

Continued from previous page

30A and 50A Residential, Commercial and Industrial Grade Power Devices

Rating	Receptacle/Plug Configuration & NEMA No.		Flush Mount Receptacle	Surface Mount Receptacle	Panel Mount Receptacle	Angle Plug	Wallplate Size
2-Pole, 3-Wire, Grounding  							
30A-125V	5-30R 	5-30P 	—	—	—	9530-P 	2.15" Center
30A-125V For Recreation Vehicles Cat. No. W7313 is WR	TT-30R 	TT-30P 	7313/W7313  Cat. No. W7313 is WR	—	—	830-T 	
30A-250V	6-30R 	6-30P 	5372/5372-IG* 	5376 	—	9630-P 	
30A-277V	7-30R 	7-30P 	9730-A 	—	—	—	
50A-125V	5-50R 	5-50P 	5373 	—	—	9550-P 	
50A-250V	6-50R 	6-50P 	5374/5374-IG* 	5378 	—	9650-P 	
50A-277V	7-50R 	7-50P 	9750-A 	—	—	9750-P 	

*Isolated Ground.

Continued on next page

Wallplates

1-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80528-W
Thermoplastic (Nylon) 80728-W
Stainless Steel 84028

2-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80526-W
Thermoplastic (Nylon) 80726-W
Stainless Steel 84026

See Wallplates section pages **S-9** and **S-10** for complete ordering information.

NOTE: Refer to instruction sheets for proper conductor size, material and torque range.

WARNING: Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Continued from previous page

30A, 50A and 60A Residential, Commercial and Industrial Grade Power Devices

Rating	Receptacle/Plug Configuration & NEMA No.	Flush Mount Receptacle	Surface Mount Receptacle	Panel Mount Receptacle	Angle Plug	Wallplate Size
3-Pole, 3-Wire, Non-Grounding						
30A-125V/250V	10-30R 	10-30P 	5207 	5054 	—	9332-P 2.15" Center
50A-125V/250V	10-50R 	10-50P 	5206 	5050 	—	9450-P
3-Pole, 4-Wire, Grounding						
30A-125V/250V	14-30R 	14-30P 	278 	55054 	—	9432-P 2.15" Center
50A-125V/250V Cat. No. W0279 is WR	14-50R 	14-50P 	279/W0279 Cat. No. W0279 is WR	55050 	279-PM 	9452-P
60A-125V/250V	14-60R 	14-60P 	9460/9460-IG* 	—	—	9462-P

*Isolated Ground.

Continued on next page

Wallplates

1-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80528-W
Thermoplastic (Nylon) 80728-W
Stainless Steel 84028

2-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80526-W
Thermoplastic (Nylon) 80726-W
Stainless Steel 84026

See Wallplates section pages **S-9** and **S-10** for complete ordering information.

NOTE: Refer to instruction sheets for proper conductor size, material and torque range.

WARNING: Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Traditional Wallplates

Power Outlet Receptacles



Continued from previous page

Power Outlet Receptacles

Standard Size Plastic, Nylon and Metal — 2-Gang

		Thermoset (Plastic)		Thermoplastic (Nylon)	Metal	
Description	Color	Cat. No.	Cat. No.	Cat. No.	Material Type	Cat. No.
	White	80526-W	80726-W	80726-W	Aluminum	83026
	Ivory	80526-I	80726-I	80726-I	Gray Painted Steel	4934
	Lt. Almond	80526-T	—	—	Stainless Steel	84026
	Black	80526-BLK	—	—	C-Series 430 S/S	SL703
	Brown	—	80726	80726	C-Series 302/304 S/S	SS703-40
	White	80530-W	—	—	Gray Painted Steel	S701-GY
	Ivory	80530-I	—	—	C-Series 430 S/S	SL701
	Lt. Almond	80530-T	—	—	C-Series 302/304 S/S	SS701-40
	Black	80530-BLK	—	—	Non-Magnetic S/S	S701-40
					Stainless Steel	84022

Note: Use with 278, 279, 5206, 5207, 5371, 5372, 5374

Standard Size Metal — 2-Gang with Centered Opening

		Metal	
Description		Material Type	Cat. No.
 1-Decora®		Non-Magnetic S/S	S746-N
 1-Toggle		Brass Non-Magnetic S/S	81040 84040-40
 1-Duplex		C-Series 430 S/S C-Series 302/304 S/S Non-Magnetic S/S	SL748 SS748-40 84039-40
 1-Outlet 1.406" dia. hole		Non-Magnetic S/S	84092-40

Standard Size Louvre

		Painted Steel	Metal	
Description	Color	Cat. No.	Material Type	Cat. No.
 1-Gang, Center Horizontal, Strap Mount	White	88079	Brass Non-Magnetic S/S	81079 84079-40
 1-Gang Vertical, Strap Mount	White	88080	Brass Non-Magnetic S/S	81080 84080-40
 2-Gang, 2-Louvre, Vertical, Strap Mount			Non-Magnetic S/S	84081-40