

Decora® Combination Devices

Decora® combination devices offer switch/switch, switch/receptacle and switch/pilot light pairings in sleek packages suitable for the finest interiors. For the ultimate in convenience and safety, the Decora® Combination Switch/SmartlockPro® GFCI receptacles pair a single pole switch with a GFCI receptacle equipped with Leviton's pioneering true dead-face design.

Sample Decora® Combination Devices



Features and Benefits

- Elegant Decora® styling provides multiple controls in a single-gang wallbox
- Impact-resistant thermoplastic and double-wipe contacts
- Common shunted internally to all switches
- Limited 2-year warranty

Tamper-Resistant Receptacles

- Shutter mechanism inside the receptacle blocks access to the contacts unless a two- or three-prong plug is inserted
- TR symbol on residential receptacles assures they meet the latest NEC requirements
- Heavy-duty construction offers long, trouble-free service life

All SmartlockPro® GFCI Combination Devices

- TEST/RESET buttons match device color
- Dual function LED indicator light — provides indication of wiring error and power availability

SmartlockPro® GFCI/Sensor Guide Light

- Manual control of sensor light using the TEST/RESET buttons
- Long-lasting, energy efficient LEDs with 20-year life expectancy — no bulbs to replace
- Light sensor provides automatic ON/OFF features

SmartlockPro® GFCI/Switch

- Replaces standard switch/outlet combination devices in residential and light commercial installations
- Permits multiple wiring options that allow for GFCI protection of switched load and downstream receptacles

Color Choices Decora® combination devices are offered in a wide range of colors. To order colors, add suffix to Cat. No.



White
(-W)



Ivory
(-I)



Light Almond
(-T)



Gray
(-G/-GY)



Black
(-E)



Brown
(-/-B)



Red
(-R)

Decora® Combination Devices

15A, 20A Combination Devices			
Rating		Switch: 15A-120VAC Receptacle: 15A-125V	Switch: 20A-120VAC Receptacle: 20A-125V
NEMA		5-15R	5-20R
Description	Color	Cat. No.	Cat. No.
Single Pole Switch/ Tamper-Resistant Receptacle	White	T5625-W	—
	Ivory	T5625-I	—
	Light Almond	T5625-T	—
	Black	T5625-E	—
Single Pole Switch/Receptacle	White	5625-W	5636-W
	Ivory	5625-I	5636-I
	Light Almond	5625-T	—
	Black	5625-E	—
	Gray	5625-GY	—
Rating		Switch: 15A-120VAC Pilot Light: 1/25W-125VAC	Switch: 20A-120VAC Pilot Light: 1/25W-125VAC
Description	Color	Cat. No.	Cat. No.
Single Pole Switch/ Pilot Light	White	5626-W	—
	Ivory	5626-I	—
Rating		15A-120/277VAC	20A-120/277VAC
Description	Color	Cat. No.	Cat. No.
Two Single Pole Switches	White	5634-W	5627-W
	Ivory	5634-I	5627-I
	Light Almond	5634-T	5627-T
	Black	5634-E	—
	Gray	5634-GY	—
	Brown	5634	5627-B
3-Way Switch/Single Pole Switch	White	5641-W	—
	Ivory	5641-I	—
	Light Almond	5641-T	—
	Black	5641-E	—
Two 3-Way Switches	White	5643-W	5640-W
	Ivory	5643-I	5640-I
	Light Almond	5643-T	5640-T
Rating		Switch: 15A-120VAC Pilot Light: 1/25W-125VAC	
Description	Color	Cat. No.	
3-Way Switch/ Receptacle	White	5645-W	—
	Ivory	5645-I	—
	Black	5645-E	—

Continued on next page



T5625-W



5626-W