

Lampholders

Fluorescent

Medium, High Output and Slimline Linear Fluorescent Lampholders

Features and Benefits

- Copper alloy contacts
- Quickwire terminals accept #18 AWG twisted and tinned, solder-dipped or solid leads
- Lampholders are white
- All NOM-ANCE certified except where indicated by °

Recessed Double Contact, Pedestal Type Lampholders

For High Output Lamps — Silver Plated Contacts, 20 Gage Panels

Description	Rating	Cat. No. Plunger	Cat. No. Fixed
Screw Mount, Push-in wiring Non-Shunted	660W 600V	13464* —	13465* —
Slide-on, Shallow Base, Quickwire Terminals Non-Shunted		13550* —	13551* —
Slide-on, Shallow Base for Power Groove and Jacketed Lamps, Quickwire Terminals Non-Shunted		13556* —	13557* —



13550



2536

For Medium Bi-Pin Lamps — Silver Plated Contacts, 20 Gage Panels

Description	Rating	Cat. No. Plunger	Cat. No. Fixed
Slide-on, Shallow Base Quickwire Terminals, G-13 Base Non-Shunted	660W 600V	13570* —	13571* —

For Slimline, Single Pin Lamps

Description	Rating	Cat. No. Plunger	Cat. No. Fixed
Shallow Base, Slide-On or Lock-On Mounting, Quickwire Terminals	660W 1000V 660W 600V	2536* —	— 2537*



2537

* Suitable for outdoor applications when properly enclosed.
NOM-ANCE Certified except where indicated by °

Continued on next page

For Medium, Single Pin Lamps

Description	Rating	Cat. No. Fixed
Pedestal type, Straight-in Wiring through Wireways or Screw Terminals	660W 600V	390-1W°



390-1W

*Suitable for outdoor applications when properly enclosed.
NOM-ANCE Certified except where indicated by °