

# **Traditional Wallplates**

Familiar and functional, Leviton traditional wallplates are designed for use with traditional Leviton devices. They represent styles and form factors that have stood the test of time. Their clean lines work in virtually any location, whether in new or retrofit construction, and they install quickly and easily. Leviton offers traditional wallplates in a vast array of colors and configurations.

# Sample Traditional Wallplates



# **Features and Benefits**

# All Leviton Wallplates

- Easy to clean, smooth finish
- Non-combustible
- Color-matched metal mounting screws supplied
- UL Listed and CSA Certified
- Conforms to NEMA and ANSI standards
- Backed by a limited 10-year warranty (except thermoset wallplates)

# Thermoset (Plastic) Wallplates (Residential Grade)

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL 514 testing requirements
- Resistant to fading, discoloration, grease, oil, organic solvents, moisture and scratches
- Backed by a limited 2-year warranty

#### Thermoplastic (Nylon) Wallplates (Residential/Commercial Grade)

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications

# Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick brushed finish
- Standard stainless steel Type 430, .032" thick, also available brushed finish
- Brass is 70/30 alloy 260, .040" thick polished or brushed finish

#### **Antimicrobial Treated Wallplates**

- Leviton has developed antimicrobial treated wiring devices to help keep the surfaces of our switches and wallplates cleaner.
- An antimicrobial additive helps to inhibit the growth of mold, mildew, fungi and odor-causing bacteria on the surface of the devices in between normal cleanings

# **Color Choices**

Traditional wallplates are offered in a wide range of colors and finishes. To order colors, add suffix to Cat. No.













Red

(-R)

Steel



(-B)



(-PB)

Continued from previous page

# **Power Outlet Receptacles**

		Thermoset (Plastic)	Thermoplastic (Nylon)	lylon) Metal	
Description	Color	Cat. No.	Cat. No.	Material Type	Cat. No.
30A and 50A	White	80526-W	80726-W	Aluminum	83026
Receptacle,	Ivory	80526-l	80726-I	Gray Painted Steel	4934
2.15" dia. hole	Lt. Almond	80526-T	_	Stainless Steel	84026
	Black	80526-BLK	_	C-Series 430 S/S	SL703
	Brown	_	80726	C-Series 302/304 S/S	SS703-40
30A and 50A	White	80530-W	_	Gray Painted Steel	S701-GY
Receptacle,	lvory	80530-l	_	C-Series 430 S/S	SL701
• 2.465" dia. hole	Lt. Almond	80530-T	_	C-Series 302/304 S/S	SS701-40
	Black	80530-BLK	_	Non-Magnetic S/S	S701-40
30A and 50A Receptacle,				Stainless Steel	84022
• 2.15" dia. hole offset					

**Note:** Use with 278, 279, 5206, 5207, 5371, 5372, 5374

Standard Size Metal — 2-Gang with Centered Opening ® ®					
	Metal				
Description	Material Type	Cat. No.			
1-Decora®	Non-Magnetic S/S	S746-N			
. 1-Toggle  ■ .	Brass Non-Magnetic S/S	81040 84040-40			
1-Duplex	C-Series 430 S/S C-Series 302/304 S/S Non-Magnetic S/S	SL748 SS748-40 84039-40			
1-Outlet 1.406" dia. hole	Non-Magnetic S/S	84092-40			

Standard Size Louvre ® ®							
	Painted Steel		Metal				
Description	Color	Cat. No.	Material Type	Cat. No.			
1-Gang, Center Horizontal, Strap Mount	White	88079	Brass Non-Magnetic S/S	81079 84079-40			
1-Gang Vertical, Strap Mount	White	88080	Brass Non-Magnetic S/S	81080 84080-40			
2-Gang, 2-Louvre, Vertical, Strap Mount			Non-Magnetic S/S	84081-40			