

# Diva dimmers, switches, and fan controls



Shown actual size: Diva preset dimmer and 1-gang Claro wallplate in White (WH).

## Product family features

- Large paddle switch with a captive linear slide dimmer for a standard Designer wallplate opening
- Preset dimmer
- LED+, reverse-phase, and 0-10V models available
- Coordinating Claro, Satin Finishes, and Stainless Steel wallplates only available separately
- All models must be derated unless otherwise noted. Visit [lutron.com/multigang](http://lutron.com/multigang) for more information.

## Control types

- Single-pole (1 location)
- 3-way or 4-way (2 or more locations)

## Direct load type compatibility

- Dimmable LED/CFL lighting (screw-base)
- Incandescent/halogen lighting
- Magnetic low-voltage lighting
- Electronic low-voltage lighting
- LED lighting
- Fluorescent lighting
- Switched lighting/fan/motor
- Ceiling fans

## Load type requiring load interface

- Neon/cold cathode lighting

Lighting load interfaces may be required for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

## Available finishes

Use **BOLD** color code in model number (Example: DVCL-153P-**BL**)

### Gloss



**WH**  
White



**LA**  
Light Almond



**AL**  
Almond



**IV**  
Ivory



**GR**  
Gray



**BR**  
Brown



**BL**  
Black

### Satin Finishes



**BW**  
Brilliant White



**GL**  
Glacier White



**SW**  
Snow



**RW**  
Architectural  
White



**LG**  
Lunar Gray



**MI**  
Mist



**PB**  
Pebble



**CS**  
Cobblestone



**SL**  
Slate



**MN**  
Midnight



**BI**  
Biscuit



**SD**  
Sand



**TP**  
Taupe



**PM**  
Pumice

### Metal wallplate\*



**CY**  
Clay



**SA**  
Sage



**EP**  
Espresso



**TF**  
Truffle



**DE**  
Deep Sea



**SR**  
Signal Red



**SS**  
Stainless Steel

\* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls.

## **3-wire LED driver/fluorescent ballast dimmers**

### Dimmers\*

3-way/single-pole	DVF-103P- <b>XX</b> <sup>1</sup>
120V 8A	DVSCF-103P- <b>XX</b> <sup>2</sup>
3-way/single-pole	DVF-103P-277- <b>XX</b> <sup>1</sup>
277V 6A	DVSCF-103P-277 <b>XX</b> <sup>2</sup>

No derating required if ganged.

Adjustable low-end trim.

## **0-10V LED/fluorescent fixture dimmers** (current sink control)

### Dimmers

3-way/single-pole	DVSTV- <b>XX</b> <sup>1</sup>
120–277V 8A	DVSCSTV- <b>XX</b> <sup>2</sup>
50mA max control current	

No power pack required.

No derating required if ganged.

## **0-10V LED/fluorescent fixture dimmers** (current sink control – power pack required)

### Dimmers\*

Single-pole	DVTV- <b>XX</b> <sup>1</sup>
30mA max control current	DVSCTV- <b>XX</b> <sup>2</sup>

Control provides dimming signal only. For dimming with on/off switching, **use with Lutron power pack**: PP-DV or PP-347H.

Compatible with any IEC 60929 Annex E compliant driver or ballast.

No derating required if ganged.

## **Tu-Wire fluorescent ballast dimmers**

### Dimmers

3-way/single-pole	DVFTU-5A3P- <b>XX</b> <sup>1</sup>
120V 5A	DVSCFTU-5A3P- <b>XX</b> <sup>2</sup>

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

**XX**<sup>1</sup>: Gloss color codes

**XX**<sup>2</sup>: Satin color codes

Wallplates not included. Order separately.

\* **Requires neutral wire connection**

## Mechanical switches



- Paddle turns on/off
- Use with any 15A load
- General purpose switching of all light sources and motor loads
- Available with locator light

### General purpose switches

#### Mechanical switches

Single-pole	CA-1PS- <b>XX</b> <sup>1</sup>
120/277V 15A	SC-1PS- <b>XX</b> <sup>2</sup>
3-way	CA-3PS- <b>XX</b> <sup>1</sup>
120/277V 15A	SC-3PS- <b>XX</b> <sup>2</sup>
4-way	CA-4PS- <b>XX</b> <sup>1</sup>
120/277V 15A	SC-4PS- <b>XX</b> <sup>2</sup>

#### Mechanical switches with locator light

Single-pole	CA-1PSNL- <b>XX</b> <sup>3</sup>
120V 15A	SC-1PSNL- <b>XX</b> <sup>4</sup>
3-way	CA-3PSNL- <b>XX</b> <sup>3</sup>
120V 15A	SC-3PSNL- <b>XX</b> <sup>4</sup>
4-way	CA-4PSNL- <b>XX</b> <sup>3</sup>
120V 15A	SC-4PSNL- <b>XX</b> <sup>4</sup>

No derating required if ganged.

**XX**<sup>1</sup>: Gloss color codes

**XX**<sup>2</sup>: Satin color codes

**XX**<sup>3</sup>: Available in Gloss White (WH), Ivory (IV), Almond (AL), and Light Almond (LA)

**XX**<sup>4</sup>: Available in Satin Finishes Snow (SW) and Biscuit (BI)

Wallplates not included. Order separately.