2.94 in (75 mm)

4.69 in (119 mm)

.30 in
(7.6 mm)
profile

Shown actual size: Luméa LED+ dimmer and
1-gang Claro wallplate in White (WH).

Product family features

- Rocker switch returns light to light level indicated by slider
- Slide up to brighten, down to dim
- LED+ model available
- Coordinating Claro wallplates only available separately
- All models must be derated unless otherwise noted. Visit **lutron.com/multigang** for more information.

Control types

☐ Single-pole (1 location)

☐ 3-way or 4-way (2 or more locations)

Direct load type compatibility

☐ Dimmable LED/CFL lighting (screw-base)

☐ Incandescent/halogen lighting

☐ Ceiling fans

Lighting load interfaces are not compatible with this family.

Available finishes

Use **BOLD** color code in model number (Example: LECL-153P-**WH**)

Gloss

WH
White

IV
Ivory

LA
Light Almond

Skylark dimmers and fan controls

2.94 in (75 mm)

4.69 in (119 mm)

.30 in
(7.6 mm)
profile

Shown actual size: Skylark dimmer and
1-gang Claro wallplate in White (WH).

Product family features

- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- LED+ models available
- Coordinating Claro and Stainless Steel wallplates only available separately
- All models must be derated unless otherwise noted. Visit **lutron.com/multigang** for more information.

Control types

Single-pole (1 location)

3-way or 4-way (2 or more locations)

Direct load type compatibility

Dimmable LED/CFL lighting (screw-base)

Incandescent/halogen lighting

Magnetic low-voltage lighting

Electronic low-voltage lighting

LED lighting

Fluorescent lighting

Ceiling fans

Ceiling fan/lights

Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

Available finishes

Use **BOLD** color code in model number (Example: SCL-153P-**GR**)

Gloss

WH
White

LA
Light Almond

AL
Almond

IV
Ivory

GR
Gray

BR
Brown

BL
Black

Metal wallplates*

SS
Stainless Steel

---

*   Stainless Steel metal wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) control.

Magnetic low-voltage dimmers

Dimmers with on/off switch

Single-pole 120 V 600 VA (450 W)	SLV-600P-**XX**[1]
3-way 120 V 600 VA (450 W)	SLV-603P-**XX**[1]

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

Electronic low-voltage dimmers

Dimmers with on/off switch*

Single-pole 120 V 300 W	SELV-300P-**XX**[1]
3-way 120 V 300 W	SELV-303P-**XX**[1]

3-wire LED driver/fluorescent ballast dimmers

Dimmers with on/off switch*

Single-pole 120 V 8 A	SF-10P-**XX**[1]
Single-pole 277 V 6 A	SF-12P-277-**XX**[1]
3-way 120 V 8 A	SF-103P-**XX**[1]
3-way 277 V 6 A	SF-12P-277-3-**XX**[1]

No derating required if ganged.

Adjustable low-end trim.

Tu-Wire fluorescent ballast dimmer

Dimmer with on/off switch

3-way/single-pole 120 V 5 A	SFTU-5A3P-**XX**[1]

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

XX[1]: Gloss color codes

Wallplates not included. Order separately.

* **Requires neutral wire connection**