#### 2.94 in (75 mm)



Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

### **Product family features**

- · Rocker switch returns light to light level indicated by slider on preset dimmers
- · Slide up to brighten, down to dim
- · LED+ models available
- · Coordinating Claro and Stainless Steel wallplates only available separately
- · All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

### **Control types**

Single-pole (1 location)

### **Direct load type compatibility**

// Dimmable LED/CFL lighting (screw-base)

Incandescent/halogen lighting

Magnetic low-voltage lighting

☐ Electronic low-voltage lighting

LED lighting

□ Fluorescent lighting

Ceiling fans

★ Ceiling fan/lights

# Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

#### **Available finishes**

Use **BOLD** color code in model number (Example: SCL-153P- $\underline{\mathbf{GR}}$ ) Gloss



Metal wallplates\*



<u>SS</u> Stainless Steel

<sup>\*</sup> Stainless Steel metal wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) control.

### **▼** Magnetic low-voltage dimmers

#### Dimmers with on/off switch

Single-pole	SLV-600P- <b>XX</b> 1
120V 600VA (450W)	
3-way	SLV-603P- <b>XX</b> 1
120V 600VA (450W)	

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

# **□** Electronic low-voltage dimmers

### Dimmers with on/off switch\*

Single-pole	SELV-300P- <b>XX</b> 1
120V 300W	
3-way	SELV-303P- <b>XX</b> 1
120V 300W	

# **⊚**/**\_=3-wire LED driver/fluorescent**

# ballast dimmers

### Dimmers with on/off switch\*

Single-pole 120V 8A	SF-10P- <b>XX</b> 1
Single-pole 277 V 6 A	SF-12P-277- <b>XX</b> ¹
3-way 120V 8A	SF-103P- <b>XX</b> 1
3-way 277V 6A	SF-12P-277-3- <b>XX</b> <sup>1</sup>

No derating required if ganged. Adjustable low-end trim.

### **Z** Tu-Wire fluorescent ballast dimmer

#### Dimmer with on/off switch

3-way/single-pole	SFTU-5A3P-XX1
120V 5A	

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

**XX**<sup>1</sup>: Gloss color codes

Wallplates not included. Order separately.

\* Requires neutral wire connection