2.86 in (73 mm)



Product family features

- · SoftGlow locator light easily identifiable in the dark
- LED+ advanced technology for superior dimming of LED, halogen and incandescent bulbs
- · Coordinating Fassada wallplates available separately
- · Visit lutron.com/dalia to learn more.

Direct load type compatibility

♥/♥Dimmable LED/CFL lighting (screw-base)

Incandescent/halogen lighting

Lighting load interfaces are not compatible with this family.

Control types

后 Single-pole (1 location)

3-way or 4-way (2 or more locations)

 $(19.3 \, \text{mm})$ profile

Available finishes

Shown actual size: Dalia dimmer and 1-gang Fassada wallplate in White (WH).

Use **BOLD** color code in model number (Example: RCL-153PNL-**LA**)

Gloss



WH White



LA Light Almond



<u>IV</u> Ivory



4.60 in (117 mm)

.76 in

BL Black

Metal wallplate*



SS Stainless Steel

Stainless Steel metal wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) controls.

Rotary dimmers and fan controls

2.86 in (73 mm)



Shown actual size: Rotary dimmer and 1-gang Fassada wallplate in White (WH).

Product family features

- · The original electronic dimmer first patented in 1959
- · Easy-turn knob adjusts light to your favorite level
- · Dual knob dimmer packages available with two finish options
- · Coordinating Fassada wallplates only available separately
- · All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

Control types

Single-pole (one location) ৰিক ি 3-way or 4-way (two or more locations)

Direct load type compatibility

Incandescent/halogen lighting

Ceiling fans

Lighting load interfaces are not compatible with this family.

Available finishes

Use **BOLD** color code in model number (Example: D-600P-IV)

Gloss







IV Ivory

Preset Dimmers



· Push to turn on/off, rotate to adjust light level

Dimmers with push on/off knob

Single-pole	D-600PH- DK
120V 600W	
3-way	D-603PH- DK
120V 600W	

Dimmers with push on/off knob and locator light

	D. 10. 000 D. 1. D. 1.
Single-pole	DNG-600PH- DK
120V 600W	
3-way	DNG-603PH- DK
120V 600W	

Fan controls with rotate on/off knob



- Rotate on/off: rotate to adjust fan speed
- · Quiet 3-speed designed to prevent motor hum (for use with only one ceiling paddle fan)
- · Fully variable models also available (for use with multiple ceiling paddle or exhaust fans)

★ Fan controls

Fan control with rotate on/off knobquiet 3-speed FSQ-2F-**DK** Single-pole 120V 1.5A

No derating required if ganged.

Fan controls with rotate on/off knob-

fully variable FS-5FH-**DK**

Single-pole

factory set minimum speed

120V 5A

User adjustable minimum speed control provides an additional wire for switching fan light (360 W, incandescent/halogen). Light turns on when fan is on, and off when fan is off.

Fully variable fan controls are commonly known as solid state fan controls.

Replacement knobs

Standard knob	RK- XX 1
---------------	-----------------

DK: Dual Knob includes one Gloss White

and one Gloss Ivory knob XX1: Gloss color codes

Wallplates not included. Order separately.