

# OCTRON® 800 XP® SUPERSAVER® ECOLOGIC®3

## EXTENDED PERFORMANCE FLUORESCENT LAMPS

The OCTRON 800 XP SUPERSAVER T8 fluorescent offering includes a full complement of lengths and wattages, ensuring there is an energy-saving lamp to satisfy nearly all applications. When these lamps are operated on Instant Start ballasts, they will provide up to 22% energy savings versus 32W lamps. At 11¢/kWh and 4000 hours of operation per year, the 22 percent energy savings translate to a savings of \$12.32 per fixture per year for a 4-lamp fixture. The initial lumen output, lumen maintenance and high color rendering of the OCTRON 800 XP SUPERSAVER/ECO3 lamps help ensure that lighting quality is maintained while energy is saved. These lamps pass the Federal TCLP test, classifying them as non-hazardous waste in most states and feature lead-free glass, bases and manufacturing process, reducing overall environmental impact.

### Key Features & Benefits

- Energy savings compared to standard 32W T8 lamp
  - 22% with the 25W XP/SS
  - 12% with the 28W XP/SS
  - 6% with the 30W XP/SS
- 94% mean lumens
- Lead free
- Dimmable (see application note 5)
- TCLP and RoHS compliant
- Retrofit lamp for existing T8 instant start systems
  - 40,000 hours rated life @ 12 hours per start
- Increased life on programmed rapid start ballasts
  - 42,000 hours rated life @ 12 hours per start

### Product Offering

Lamp Type	Wattage	CCT
F032/25W/800XP/SS/ECO3	25	3500K, 4100K, 5000K
F028/800XP/SS/ECO3	28	3000K, 3500K, 4100K, 5000K
F030/800XP/SS/ECO3	30	3000K, 3500K, 4100K,

SYLVANIA OCTRON ECOLOGIC3 T8 fluorescent lamps pass the Federal Toxic Characteristic Leaching Procedure (TCLP)<sup>1</sup> criteria for classification as non-hazardous waste in most states<sup>2</sup>.

ECOLOGIC3 represents a more comprehensive approach to sustainability encompassing high efficiency, long life and RoHS/TCLP compliance.

1. TCLP test results are based on NEMA LL Series standards and are available on request.

2. Lamp disposal regulations may vary; check your local & state regulations.



### Application Information

#### Applications

- Cove
- Direct/indirect luminaires
- Recessed troffers
- Schools
- Valance

#### Application Notes

1. FO32/25, FO28 and FO30 SUPERSAVER lamps are recommended to be used on F32T8 instant start ballast with minimum open circuit voltage of 550V RMS at the lamp.
  - a. Electronically ballasted fixture configurations which operate lamps remotely, such as Master/Satellite applications, can cause reduction of lamp open circuit voltage, in the remote fixture, below the minimum required for reliable lamp starting. For more information, please call 1-800-LIGHTBULB and ask for Ballast Technical Assistance or call your fixture manufacturer.
  - b. Not recommended to be used: (1) in remotely ballasted fixtures with lamp open circuit voltages below 550V, (2) in air handling fixtures, (3) inverter operated emergency lighting systems unless any of the above equipment is specifically listed for SUPERSAVER (SS) lamps. Any of the above situations could result in lamp starting and stabilization problems, or system compatibility issues.
2. If a 28W SUPERSAVER lamp is exposed to drafts or the ambient temperature falls below 60°F (70°F for 25W), striation (a rhythmic pulsing pattern of light running down the tube) and/or reduction in lamp brightness may occur. While visually disconcerting, neither behavior is damaging to the lamp and removing the cause (draft or temperature) will return the lamp to normal operation.
3. Fixture must conform to the latest version of the ANSI C78.81-2010 requirements for luminaire design.
4. Contact LEDVANCE for approved dimming ballasts



This light source meets restrictions on hazardous substances.



Catalog #	Type
Project	
Comments	
Prepared by	

## Ordering Information

Item Number	Ordering Abbreviation	Watts	Nominal Length (in)	Initial Lumens	Mean Lumens <sup>1</sup>	Lumens per Watt	Average Rated Life				CCT	CRI
							Instant Start 3 hrs/start	12 hrs/start	Programmed Start 3 hrs/start	Rapid Start 12 hrs/start		
OCTRON® 800 XP® SUPERSAVER®												
22233	F032/25W/835/XP/SS/EC03	25	48	2500	2350	100	24,000	40,000	40,000	42,000	3500K	85
22234	F032/25W/841/XP/SS/EC03	25	48	2500	2350	100	24,000	40,000	40,000	42,000	4100K	85
22235	F032/25W/850/XP/SS/EC03	25	48	2500	2350	100	24,000	40,000	40,000	42,000	5000K	81
22177	F028/830/XP/SS/EC03	28	48	2725	2560	97	24,000	40,000	40,000	42,000	3000K	85
22178	F028/835/XP/SS/EC03	28	48	2725	2560	97	24,000	40,000	40,000	42,000	3500K	85
22179	F028/841/XP/SS/EC03	28	48	2725	2560	97	24,000	40,000	40,000	42,000	4100K	85
22184	F028/850/XP/SS/EC03	28	48	2725	2560	97	24,000	40,000	40,000	42,000	5000K	81
22063	F030/830/XP/SS/EC03	30	48	2850	2680	95	24,000	40,000	40,000	42,000	3000K	85
22060	F030/835/XP/SS/EC03	30	48	2850	2680	95	24,000	40,000	40,000	42,000	3500K	85
22062	F030/841/XP/SS/EC03	30	48	2850	2680	95	24,000	40,000	40,000	42,000	4100K	85


1. Measured at 40% of rated life.

## Ordering Guide

F0	30	/	8	35	XP	/	SS	/	EC03
Fluorescent	Actual Wattage		Actual CRI	Color Temperature	XP = Extended Performance		SUPERSAVER		ECOLOGIC3
OCTRON	25, 28, 30		81 or 85	30 = 3000K CCT, 35 = 3500K CCT 41 = 4100K CCT, 50 = 5000K CCT					

## Lamp Dimensions

Lamp Type	(A) Max. Overall Length (in.)	(B) Base Face to Opposite Pin (in.)	(C) Max. Base Face to Base Face (in.)	(D) Max. Outside Diameter (in.)
F032/25W F028 F030	47.78	Min. 47.41 Max. 47.50	47.22	1.1



## Sample Specification

Lamp shall be OCTRON® 800 XP® SUPERSAVER® ECOLOGIC®3 (25W, 28W, 30W) lamp having medium bi-pin bases. Lamp shall be designed to pass the Federal TCLP test in force at the time of manufacture. Lamps shall have initial lumens of (2500, 2725, 2850,), mean lumens of (2350, 2560, 2680) and a correlated color temperature of (3000, 3500, 4100 or 5000) Kelvin. Lamp shall have an average rated life of (24,000, 40,000, 42,000) on (instant start, programmed rapid start) ballasts, 94% lumen maintenance at 40% of rated life and a CRI of (85, 81). The OCTRON XP SUPERSAVER ECOLOGIC3 lamp shall be operated on electronic, high frequency ballasts.

LEDVANCE LLC

181 Ballardvale Street, Suite 203

Wilmington, MA 01887 USA

Phone 1-800-LIGHTBULB (1-800-544-4828)

www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.  
All other trademarks are those of their respective owners.  
Licensee of product trademark SYLVANIA in general lighting.  
Specifications subject to change without notice.



SCAN TO FOLLOW US  
ON SOCIAL MEDIA