

DULUX® L ECOLOGIC®

T5 Compact Fluorescent Lamps

SYLVANIA DULUX L T5 lamps are high lumen, single-ended twin-tube lamps that provide lumen outputs similar to 2', 3' and 4' linear fluorescent lamps, yet are half the length. With lumen outputs up to 4800 and lamp efficacies up to 87 lumens per watt, these compact lamps can be used in indirect as well as direct applications.

QUICKTRONIC ballasts are available to operate FT18DL, FT24DL, FT36DL, FT40DL/RS and FT55DL lamps. The QUICKSENSE circuitry in these ballasts provides the end-of-life protection required by NEMA* for these lamps.

Benefits and Features

- High lumen single-ended twin-tube lamps
- 18 through 55 Watts
- 2' x 2' fixture provides equal lumen output to a 2' x 4' fixture
- 55 Watt lamps provide high lumen output for indirect and higher mounting height applications
- 3000K, 3500K, 4100K
- Excellent color rendition, CRI of 82

Application Usage

- Indirect fixtures
- Landscape lighting
- Portable sports lighting
- Recessed and surface mounted fixtures
- Sign lighting
- Stage and set lighting
- Task lighting
- Wall sconces, wall washing fixtures



Product Offering

Description	Watts	Lumens
FT18DL	18	1250
FT18DL/RS	18	1250
FT24DL	24/27	1800
FT36DL	36/39	2900
FT40DL/RS	40	3150
FT55DL	55	4800

SYLVANIA DULUX L ECOLOGIC fluorescent lamps are designed to pass the Federal Toxicity Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states.



CF029R11 9-23



Specification Data

Catalog #	Type
Project	
Comments	
Prepared by	

Ordering Guide

FT	40	DL	/	8	35	/	RS	/	ECO
Fluorescent Tubular	Wattage: 18, 24, 36, 40 & 55	DULUX Long		8 = 82 CRI	30=3000K 35=3500K 41=4100K 50=5000K		Rapid Start		ECOLOGIC®

Ordering Information

Item Number	Ordering Abbreviation	Watts	Lumens	Avg. Rated Life (hrs.)	Color Temp.	CRI	Base
20587	FT18DL/830/ECO	18	1250	12,000	3000K	82	2G11
20588	FT18DL/835/ECO	18	1250	12,000	3500K	82	2G11
20589	FT18DL/841/ECO	18	1250	12,000	4100K	82	2G11
20594	FT18DL/835/RS/ECO	18	1250	20,000	3500K	82	2G11
20597	FT24DL/830/ECO	24	1800	12,000	3000K	82	2G11
20580	FT24DL/835/ECO	24	1800	12,000	3500K	82	2G11
20596	FT24DL/841/ECO	24	1800	12,000	4100K	82	2G11
20581	FT36DL/830/ECO	36	2900	12,000	3000K	82	2G11
20582	FT36DL/835/ECO	36	2900	12,000	3500K	82	2G11
20583	FT36DL/841/ECO	36	2900	12,000	4100K	82	2G11
20584	FT40DL/830/RS/ECO	40	3150	20,000*	3000K	82	2G11
20585	FT40DL/835/RS/ECO	40	3150	20,000*	3500K	82	2G11
20586	FT40DL/841/RS/ECO	40	3150	20,000*	4100K	82	2G11
20576	FT40DL/850/RS/ECO	40	3150	20,000*	5000K	82	2G11
20590	FT55DL/830/ECO	55	4800	12,000	3000K	82	2G11
20591	FT55DL/835/ECO	55	4800	12,000	3500K	82	2G11
20592	FT55DL/841/ECO	55	4800	12,000	4100K	82	2G11


* Avg. Rated Life on instant start ballast = 15,000 hrs.
 ** At rated line voltage and nominal lamp current at 25kHz

System Comparison

Lamp Type	No. of Lamps	System Watts	Ballast Factor	System Lumens	Mean System Lumens	Mean LPW
FB40/CW/SS ES MAG	2	72	.88	4576	3890	54
FB40/700 Std. MAG	2	96	.95	5795	5100	53
FB40/700 ES MAG	2	86	.95	5795	5216	61
FBO31/800 IS	3	84	.90	7358	6769	81
FBO31/800 PLUS	3	109	1.18	9647	8875	81
FT40DL/800 40DL	3	110	.96	9072	8165	74

Lamp Dimensions

Ordering Abbreviation	(A) MOL in. (mm)	(B) Lamp Width in. (mm)	(C) Max. Bulb Diameter in. (mm)
FT18DL	9.0 (225.0)	1.6 (40.0)	0.8 (20)
FT18DL/RS	10.5 (268.0)	1.6 (40.0)	0.8 (20)
FT24DL	12.9 (320.0)	1.6 (40.0)	0.8 (20)
FT36DL	16.6 (415.0)	1.6 (40.0)	0.8 (20)
FT40DL	22.4 (570.0)	1.6 (40.0)	0.8 (20)
FT55DL	21.1 (535.0)	1.6 (40.0)	0.8 (20)
FT50DL	22.6 (570.0)	1.6 (40.0)	0.8 (20)



Sample Specification

Lamp(s) shall be DULUX® L T5 lamp(s). Lamp(s) shall have a correlated color temperature of (3000K, 3500K, 4100K, 5000K) and a CRI of 82. The DULUX L T5 (18, 24, 36, 40, 55) shall be operated on electronic high frequency ballasts with end of life circuitry.

Application Information

1. The FT18DL and FT18DL/RS lamps are not electrically interchangeable.
2. The FT24DL, FT36DL and FT40DL/RS lamps: various methods of operation (preheat, rapid start, instant start, programmed start) possible.
3. Lamp life may vary with method of operation.
4. FT24DL: 27W on RS ballasts.
5. FT36DL: 39W on RS ballasts.

LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.
All other trademarks are those of their respective owners.
Licensee of product trademark SYLVANIA in general lighting.
Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA

