



# Evergy Approved Products for KCP&L/Westar Service Areas

## Single Position Meter Sockets

100-320 Amps | UL Listed



U7043-XL-TG-KK-IL-5T9W



U9551-RXL-5T9-IL



U4013-X-2/K7-IL

### 100 & 200 Amps | 5 Terminals | Horn Bypass | Residential

Catalog Number	Amps	Phase	Application	Dimensions		
				D"	W"	H"
■ U7043-XL-TG-KK-IL-5T9W	100	1Ø3W or 3Ø3W	OH/UG	4 <sup>21</sup> / <sub>25</sub>	13	15½
■ U7043-XL-TG-KK-IL-5T9W	200	1Ø3W or 3Ø3W	OH/UG	4 <sup>21</sup> / <sub>25</sub>	13	15½

### 200 Amps | Lever Bypass | Commercial

Catalog Number	Amps	Phase	Application	Dimensions		
				D"	W"	H"
■ U9551-RXL-5T9-IL	200	1Ø3W or 3Ø3W	OH/UG	4 <sup>21</sup> / <sub>25</sub>	13	19
■ U9701-XL-IL-EVE	200	3Ø4W	OH/UG	4 <sup>21</sup> / <sub>25</sub>	13	19

### 320 Amps | Lever Bypass | Commercial & Residential

Catalog Number	Amps	Phase	Application	Dimensions		
				D"	W"	H"
■ U4702-X-5T9-K3-K2-IL <sup>1</sup>	320	1Ø3W or 3Ø3W	OH/UG	4 <sup>21</sup> / <sub>25</sub>	15	28¼
■ U4013-X-2/K7-IL	320	3Ø4W	OH/UG/SW	6½	17¾	40½

## Notes

- **Connectors:** Extruded aluminum connectors are tin plated. **U9551** unit includes removable bonding strap for isolated neutral.
- Stocked item (availability subject to change).
- <sup>1</sup> Max. line side conductor size is (1) or (2) 250 kcmil.

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

