

DUAL-SIDE ENTRY, CON'T

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IT-500	500 - 4	2	2.90	2.83	2.95	350-430	5/16
IPLD500-3		3	4.04	2.83	2.95	350-430	5/16
IPLD500-4		4	5.19	2.83	2.95	631-806	5/16
IPLD500-5		5	6.33	2.83	2.95	631-806	5/16
IPLD500-6		6	7.48	2.83	2.95	946-1209	5/16
IPLD500-8		8	9.77	2.83	2.95	1262-1612	5/16
IPLD500-10		10	12.06	2.83	2.95	1262-1612	5/16
IPLD500-12		12	14.35	2.83	2.95	1262-1612	5/16
IPLD500-14		14	16.64	2.83	2.95	1262-1612	5/16
IT-600	600 - 6	2	3.20	3.14	3.30	385-475	5/16
IPLD600-3		3	4.50	3.14	3.30	385-475	5/16
IPLD600-4		4	5.80	3.14	3.30	810-1035	5/16
IPLD600-5		5	7.10	3.14	3.30	810-1035	5/16
IPLD600-6		6	8.40	3.14	3.30	1215-1554	5/16
IPLD600-8		8	11.00	3.14	3.30	1620-2070	5/16
IPLD600-10		10	13.60	3.14	3.30	1620-2070	5/16
IPLD600-12		12	16.20	3.14	3.30	1620-2070	5/16
IPLD600-14		14	18.77	3.14	3.30	1620-2070	5/16
IPLD600-16		16	21.37	3.14	3.30	1620-2070	5/16
IPLD600-18		18	23.97	3.14	3.30	1620-2070	5/16
IT-750*	750 - 1/0	2	3.48	3.41	3.46	385-475	3/8
IPLD750-3*		3	4.90	3.41	3.46	385-475	3/8
IPLD750-4*		4	6.33	3.41	3.46	930-1178	3/8
IPLD750-5*		5	7.75	3.41	3.46	930-1178	3/8
IPLD750-6*		6	9.18	3.41	3.46	1395-1767	3/8
IPLD750-8*		8	12.03	3.41	3.46	1860-2356	3/8
IPLD750-10*		10	14.88	3.41	3.46	1860-2356	3/8
IPLD750-12*		12	17.73	3.41	3.46	1860-2356	3/8
IPLD750-14*		14	20.58	3.41	3.46	1860-2356	3/8

DUAL-SIDE ENTRY, DOUBLE SCREW

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITH-750**	750 - 1/0	2	3.48	4.46	3.42	435-535	5/16
IPLDH750-3**		3	4.90	4.46	3.42	435-535	5/16
IPLDH750-4**		4	6.33	4.46	3.42	930-1178	5/16
IPLDH750-5**		5	7.75	4.46	3.42	930-1178	5/16
IPLDH750-6**		6	9.18	4.46	3.42	1395-1767	5/16
IPLDH750-8**		8	12.03	4.46	3.42	1860-2356	5/16
IPLDH750-10**		10	14.88	4.46	3.42	1860-2356	5/16
IPLDH750-14**		14	20.63	4.46	3.42	1860-2356	5/16