

## CFLi LAMP SHAPES

A bulb designation consists of a letter(s) to indicate the shape and a figure to indicate the approximate major diameter in eighths of an inch. For example, an A19 bulb is an Aline, 19/8 of an inch in diameter.



Aline



Micromini



Mini



Super mini



Twist



3-Way Twist



R20




BR30



BR40



PAR38



PAR38 HG



B10



G25



A15



Bullet

## BASE IDENTIFICATION



Med Base



Candelabra



GU24

## HOW TO READ PRODUCT INFORMATION – COMPACT FLUORESCENT

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg rated life (hrs)	CCT	CRI	Approx. Lumens at 25°C/77°F	Notes
-----------------	------------	----------	------	----------------	-----------------------	---------	----------------------	-----	-----	-----------------------------	-------

**Bulb** Describes the shape of the bulb.

**Base** Base designations for compact fluorescent lamps are the NEMA designations.

**Symbols & Footnotes** Most symbols and footnotes that apply to a specific product will appear in this space. The explanations of the symbols and footnotes are at the end of the compact fluorescent section.

**Ordering Abbreviation** A text description of the lamp. Please see below for an example and explanation of the code.

**NEMA Generic Designation** Designation assigned by NEMA (National Electrical Manufacturers Association).

**CCT** Correlated Color Temperature. Measured in degrees Kelvin (K).

**CRI** Color Rendering Index. A numbering system for rating the relative color rendering quality of a light source compared to a standard.

**Initial Lumens** Initial lumens are measured when the lamp has been operating for 100 hours. Compact Fluorescent lamp lumens are measured at 25°C (77°F) and 35°C (95°F).

### How to Read Ordering Abbreviations

CF23EL/MICRO/827/LS/RP2

CF	Compact Fluorescent
23	Nominal lamp wattage
EL	Electronic Lamp
MICRO	Type of bulb
827	'8' denotes CRI in the 80's. '27' 2700K CCT
LS	Living Spaces™
RP2	Retail Two Pack

### LAMP DISPOSAL LABELING

The following information appears on the packages of fluorescent lamps.



For weight and measurement information, please visit [www.sylvania.com](http://www.sylvania.com)



DULUX S/E



DULUX D/E

## Compact Fluorescent Lamps

### DULUX® S/E 4-Pin Single-Tube Compact Fluorescent – For Dimming and Electronic Ballast

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Notes
7	S (T4)	4.5	115	267	20312	CF7DS/E/827	50	20000	2700	82	400 (360)	1,2,4,5,9
					20316	CF7DS/E/841	50	20000	4100	82	400 (360)	1,2,4,5,9
9	S (T4)	5.7	145	267	20313	CF9DS/E/827	50	20000	2700	82	580 (520)	1,2,4,5,9
					20317	CF9DS/E/841	50	20000	4100	82	580 (520)	1,2,4,5,9
13	S (T4)	6.2	157	2GX7	20314	CF13DS/E/827	50	10000	2700	82	800 (720)	1,2,4,5,9
					20284	CF13DS/E/830	50	10000	3000	82	800 (720)	1,2,4,5,9
					20318	CF13DS/E/841	50	10000	4100	82	800 (720)	1,2,4,5,9

### DULUX® S Preheat 2-Pin Single-Tube Compact Fluorescent – With Starter in Base for Magnetic Ballasts

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Notes
5	S (T4)	4.21	107	G23	21279	CF5DS/827/ECO	50	10000	2700	82	230 (210)	1,3,5,9,11
					21278	CF5DS/841/ECO	50	10000	4100	82	230 (210)	1,3,5,9,11
7	S (T4)	5.31	135	G23	21277	CF7DS/827/ECO	50	10000	2700	82	400 (360)	1,3,5,9,11
					21276	CF7DS/835/ECO	50	10000	3500	82	400 (360)	1,3,5,9,11
					21274	CF7DS/841/ECO	50	10000	4000	82	400 (360)	1,3,5,9,11
					21275	CF7DS/850/ECO	50	10000	5000	82	400 (360)	1,3,5,9,11
					21272	CF9DS/827/ECO	50	10000	2700	82	580 (520)	1,3,5,9,11
9	S (T4)	7.09	180	G23	21273	CF9DS/835/ECO	50	10000	3500	82	580 (520)	1,3,5,9,11
					21270	CF9DS/841/ECO	50	10000	4100	82	580 (520)	1,3,5,9,11
					21271	CF9DS/850/ECO	50	10000	5000	82	580 (520)	1,3,5,9,11
					21136	CF13DS/827/ECO	50	10000	2700	82	800 (720)	1,3,5,9,11
13	S (T4)	7.09	180	GX23	21133	CF13DS/830/ECO	50	10000	3000	82	800 (720)	1,3,5,9,11
					21137	CF13DS/835/ECO	50	10000	3500	82	800 (720)	1,3,5,9,11
					21134	CF13DS/841/ECO	50	10000	4100	82	800 (720)	1,3,5,9,11
					21135	CF13DS/850/ECO	50	10000	5000	82	800 (720)	1,3,5,9,11

### DULUX D/E 4-Pin SUPERSAVER® ECOLOGIC® Double-Tube Compact Fluorescent Lamps – For Dimming and Electronic Ballast

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Notes
15	D (T4)	5.79	147	G24Q-2	20224	CF18DD/E/15W/SS/830/ECO	50	20000	3000	82	1125 (970)	1,2,4,5,9
					20225	CF18DD/E/15W/SS/835/ECO	50	20000	3500	82	1125 (970)	1,2,4,5,9
					20226	CF18DD/E/15W/SS/841/ECO	50	20000	4100	82	1125 (970)	1,2,4,5,9
21	D (T4)	6.54	166	G24Q-3	20457	CF26DD/E/21W/SS/830/ECO	50	20000	3000	82	1525 (1310)	1,2,4,5,9
					20458	CF26DD/E/21W/SS/835/ECO	50	20000	3500	82	1525 (1310)	1,2,4,5,9
					20459	CF26DD/E/21W/SS/841/ECO	50	20000	4100	82	1525 (1310)	1,2,4,5,9

For the current listing of available products and more complete product information, please visit us at [www.sylvania.com](http://www.sylvania.com).

Specifications subject to change without notice.