# 4S Deep & Extra Deep Boxes | A11

4" SQUARE (4S) DEEP BOXES WELDED

2-1/8" DEEP

30.3 Cu. In.


WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS


#### **NOTE**


► For Fixture/Luminaire Support of 50 lbs or less

Cat.	Bracket &	Knockout	Std.		
No.	Setback	Sides	Bottom	Pkg.	
4SDB-NM	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	24	
*4SDB-NM-B	B, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24	
4SDB-NM-FB	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24	
*4SDB-NM-WB	WB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24	









### 4" SQUARE (4S) EXTRA DEEP BOXES

WELDED

3-1/2" DEEP

46.0 Cu. In.

#### **PRODUCT FEATURES**


- Durable Red Powder Coat Finish for FA Series
- UMAB & UMIAB's mount direct-to -stud or used with the SSB-T5 or SSB-TBAR for between stud or ceiling installation (see pg. P1 for more info.)
- UMAB's depth adjusted via screws outside of the box
- UMIAB's depth adjusted via screws inside the box


#### **NOTE**

 For Fixture/Luminaire Support of 50 lbs or less (except UMAB's & UMIAB's)

Cat.	Bracket &	Knocke	Std.	
No.	Setback	Sides	Bottom	Pkg.
4SEDB-CKO	-	12 - CKO	4 - CKO	24
FA-4SEDB-CKO	-	12 - CKO	4 - CKO	24
*4SEDB-CKO-FB	FB,1/2" thru 1-1/4"	10 - CKO	4 - CKO	10
*FA-4SEDB-CKO-FB	FB,1/2" thru 1-1/4"	10 - CKO	4 - CKO	10
UMAB	Stud-mount, adjustable 0" to 1-1/2	." 12 - CKO	4 - CKO	10
FA-UMAB	Stud-mount, adjustable 0" to 1-1/2	." 12 - CKO	4 - CKO	10
UMIAB-35 NEW	Stud-mount, adjustable 1/2" to 1-1/	2" 12 - CKO	4 - CKO	10
FA-UMIAB-35 NEW	Stud-mount, adjustable 1/2" to 1-1/	2" 12 - CKO	4 - CKO	10

















- 600V MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Acceptable for use in 2-hour rated walls
- Visit www.ul.com or QCIT Guide on page W1 for more information





## **A24** Fire Alarm and Life Safety Products



#### **FIRE ALARM BOXES & COVERS**

#### **PRODUCT FEATURES**

- ▶ Provide easy identification of products containing cabling of Fire Alarm Systems
- Prevent need for repainting
- ▶ Industrial, Commercial or Residential Use
- Durable Red Powder Coat Finish

#### **NOTE**

- Additional specs located with corresponding models without red finish in catalog
- All 4S Boxes are certified for Fixture/Luminaire Support of 50 lbs or less (except for UMAB & UMIAB)
- ▶ 600V MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Acceptable for use in 2-hour rated walls (4S Box only)
- Visit www.ul.com or QCIT Guide on page W1 for more information

Cat.		Knockouts		
No.	Description	Sides	Bottom	Pkg
*FA-4RBC	Red 4" Octagon Blank Cover	-	-	50
FA-4BC	Red 4" Square Blank Cover	-	-	50
FA-4SB-MKO	Red 4" Square, 1-1/2" Deep Box	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	50
FA-4SB-MKO-EXT	Red 4" Square, 1-1/2" Deep Extension	8 - 1/2", 4 - MKO	-	50
FA-4SDB-75	Red 4" Square, 2-1/8" Deep Box	8 - 3/4"	2 - 1/2", 2 - MKO	24
FA-4SDB-MKO	Red 4" Square, 2-1/8" Deep Box	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
FA-4SDB-MKO-FB	Red 4" Square, 2-1/8" Deep Box w/ FB Brack	et 6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
FA-4SEDB-CKO	Red 4" Square, 3-1/2" Deep Box	12 - CKO	4 - CKO	24
*FA-4SEDB-CKO-FB	Red 4" Square, 3-1/2" Deep Box w/ FB Brack	et 10 - CKO	4 - CKO	10
FA-UMAB	External Adjustment Red 4" Square, 3-1/2" De Box, 46 Cu. In., Adj. range: 0" to 1-1/2"	eep 12 - CKO	4 - CKO	10
FA-UMIAB-35 NEW	Internal Adjustment Red 4" Square, 3-1/2" Dec Box, 46 Cu. In., Adj. range: 1/2" to 1-1/2"	ep 12 - CKO	4 - CKO	10
FA-UMAB-4R	External Adjustment Red 4" (4O), 2-1/8" Deep Box, 21.1 Cu. In., Adj. range: 0" to 1-1/2"	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	20
FA-5BC	Red 4-11/16" Square Blank Cover	-		50
FA-5SDB-MKO	Red 4-11/16" Square, 2-1/8" Deep Box	2 - 1/2", 10 - MKO	2 - 1/2", 2 - 3/4"	24



\*FA-4RBC



FA-4BC



FA-4SB-MKO



FA-4SB-MKO-EXT



FA-4SDB-75



FA-4SDB-MKO



FA-4SDB-MKO-FB



FA-4SEDB-CKO



\*FA-4SEDB-CKO-FB



FA-UMAB



FA-UMIAB-35



FA-UMAB-4R



FA-5BC



FA-5SDB-MKO

#### **UNIVERSAL CUT-IN BOX ADAPTER**

### **PRODUCT FEATURES**

- ▶ Quickly mount any 4" square steel junction box into old work applications
- Works with 4" square boxes of any depth
- ▶ Two integrated old work steel clips with screws
- ▶ For drywall or other wall materials
- Small footprint easily concealed by life safety devices greater than 4-7/8" W X 4-3/4" H
- Available in Red powder coat finish for FA circuits

Visit our website to download a wall mounting template

Cat. No.	Description	Std.Pkg.
UCIA-4S NEW	Cut-in adapter for 4" Square Boxes	20
FA-UCIA-4S NEW	Red Cut-in adapter for 4" Square Boxes	20

#### Turn any 4" square box into an "Old Work" box!



UCIA-4S



FA-UCIA-4S



**FIRE ALARM** 






**PREFABRICATION** 

UCIA-4S in the shop






#### **BOX & ADAPTER LATCHES**



#### **BOX TO ADAPTER LATCH**

Bendable latch tabs securely hold 4" or 4-11/16" sq. box in place without need to tighten box screws. Skip hassle of tightening box screws until the final ring installation, making installation process more efficient and convenient.



#### ADAPTER TO BRACKET LATCH

Fold tab to secure adapter on SSB Brackets

#### 90° ROTATION



Extended Mounting Tab enables secure mounting with 90° rotation Box will be able to receive large conduit without removal of back support



All \*AR1G- & \*AR2G- rings install vertical or horizontal

#### **STUD MOUNT**

## SIMPLE SUPPORT BRACKET

#### PRODUCT FEATURES

- Adjusts from 15" to 25", rigidity eliminates need for farside back support
- ► Accepts 4", 4-11/16" & 5" Sq. Boxes; must be paired with UMA-LVBS to mount 5" Sq. Boxes
- Expand without removing adapters or junction boxes (ideal for prefabrication)
- Install between wall studs or overhead between hard lid ceiling joists
- Must be accompanied with either UMA or UMA-LVBS to mount a junction box. UMAB's/UMIAB's also snap on
- See pg. P1 for complete SSB Family of products









Fits 5" square boxes!

# 4" Box 4-11/16" Box 5" Box

#### **ANY SIZE J-BOX**

SSB-T5 fits up to three 4", 4-11/16" or 5" boxes between 24" studs

#### VERTICAL & HORIZONTAL RING INSTALLATION


UMA: 4" & 4-11/16" sq. box adapter compatible with all Adjustable Rings

Mounting hole and center cutout for a quick, leveled installation

Adapter slides until set w/
Tek Screw

Adjustable 15" to 25"

Order preassembled with box and 10" pigtail as SSB-4S-MKO, SSB-A4, SSB-5S-MKO or SSB-T5B-200 (pg. P5-6)



#### SSB-T5 INSTALLED

Use **5SLB-2MKO** (pg. P28) or **T5B**'s (pg. P27) for 1-1/4" or larger conduit



#### POWER + DATA

Use LVSB1 or 2 for Low Voltage applications that do not require a junction box



## **READY-TO-INSTALL BOXES & BRACKETS**

IN-STOCK, PRE-ASSEMBLED ROUGH-IN PRODUCTS

	Cat No.	Std. Installa	Installation Image		Cat No.	Std. Pkg	Installation Image	
	UMAB	10		NEW	Town			
ARM	FA-UMAB	10 Adjustable 0" to 1-1/2"		NEW F	A-UMIAB-35	10	Adjustable 1/2" to 1-1/2"	
	Cat No.	Comp	onents	Std. Pkg	Insta		llation Images	
FIRE ALARM	FA-SSB-UMAB	SSB-T5	FA-UMAB	10				
	FA-TBAR-UMAB	SSB-TBAR	FA-UMAB	10				
OR.	FA-UMAB-4R	-	-	20		0 0		
SMOKE	FA-SSB-4R	SSB-T5	FA-UMAB-4R	20		Direct-to-Stud		
* BO	FA-TBAR-4R	SSB-TBAR	FA-UMAB-4R	20			TOL	
LIGHTING	UMAB-4R	-	-	20	FA-SSB-4R Shown Ins in hard lid ceiling		nstalled UMAB-4R Shown Installed on SSB-T5	
LIGH	SSBT-4R	SSB-TBAR	UMAB-4R	20	FA-TBAR-4R and SSBT-4R Shown Installed in T-Bar ceiling			
MULTI-GANG	SSB-MB3 (Shown)	SSB-T5	MB-3	10				







## P1 | SSB System

#### SIMPLE SUPPORT **BRACKETS FAMILY**

#### **PRODUCT FEATURES**

- ▶ SSB Brackets adjust from 15" to 25", rigidity eliminates need for farside back support
- ▶ SSB Brackets accept 4", 4-11/16" & 5" Sq. Boxes; must be paired with UMA-LVBS to mount 5" Sq. Boxes
- ▶ SSB Brackets expand without removing adapters or junction boxes (ideal for prefabrication)
- \*SSB-T5 installs between wall studs or overhead between hard lid ceiling joists
- ▶ SSB-TBAR includes two riveted clips for T-bar drop ceiling installation
- Must use **5SLB-2MKO** (pg. P28) or T5B's (pg. P27) with SSB Brackets for 1-1/4" or larger conduit
- ► UMA, UMA-LVBS's, UMAB's & UMIAB's either mount direct-tostud or clip onto SSB Brackets
- ▶ UMA compatible with all Orbit Adj. Rings
- ▶ UMA-LVBS's compatible with all Orbit Adj. Rings except for \*SAR2G models; allows for \*AR2G-58 models to mount vertical or horizontal
- ▶ UMA-LVBS's allow 4" rings to be mounted independently of boxes,
- can be used with any size box bundal's & UMIAB's ship with boxes set at 5/8" raise
- ▶ UMAB's & UMIAB's are ideal for Life Safety systems rough-in
- LVSB1 & LVSB2 eliminate need for an electrical box in low voltage applications on SSB Brackets
- See pg. P2 P8 for more SSB System Product Features

#### NOTE

- ▶ SSB Brackets must be accompanied with either UMA or UMA-LVBS's to mount a junction box. UMAB's/UMIAB's also snap onto SSB Brackets.
- ▶ Made in USA SSB-T5 available upon request









Cat. No.	Description Std. I	Pkg.
*SSB-T5	Simple Support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" to 25" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 15" for mounting 4", 4-11/16" & 5" Sq. boxes between students of the support Bracket adjusts from 1	25
SSB-TBAR	SSB-T5 with T-bar Drop Ceiling Mounting Clips	20
UMA	Universal Mounting Adapter for 4" and 4-11/16" Sq. boxes & multigang boxes to mount to SSB-T5, SSB-TBAR, USB and directly to stud. Break in half to mount multigang boxes	25
*UMA-LVBS	Universal Mounting Adapter w/ Back Support (up to 6"), allows for 4", 4-11/16" & 5" Sq. boxes to mount to SSB-T5, SSB-TBAR, USB and directly to stud	25
*US-UMA-LVB	S (IEV) Made in USA UMA-LVBS	25
UMIAB-35 NE	Dinternal Adjustment 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 1/2" to 1-1/2"	10
FA-UMIAB-35	Internal Adjustment Red 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 1/2" to 1-1/2"	10
UMAB	External Adjustment 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 0" to 1-1/2"	10
FA-UMAB	External Adjustment Red 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 0" to 1-1/2"	10
UMAB-4R	External Adjustment 4" (4O), 2-1/8" Deep Box w/ 10" PT, 21.1 Cu. In., Adj. range: 0" to 1-1/2"	20
FA-UMAB-4R	External Adjustment Red 4" (40), 2-1/8" Deep Box, 21.1 Cu. In., Adj. range: 0" to 1-1/2"	20
LVSB1	Low Voltage Stud Mounting Bracket 1-Gang, 1/2" raise	50
LVSB2	Low Voltage Stud Mounting Bracket 2-Gang, 1/2" raise	25
BMCS	Box Mounted Conduit/Cable Support	50
BMCS-CJ6	Box Mounted Conduit/Cable Support w/ CS-CJ6 installed	50

\*UMA-LVBS Spec updated May 2023





SSB-TBAR



\*SSB-T5

Break in half to mount Multigang Boxes

**UMA** 



\*UMA-LVBS \*US-UMA-LVBS



UMIAB-35



FA-UMIAB-35



**UMAB** 



FA-UMAB



UMAB-4R



FA-UMAB-4R





LVSB2



**BMCS** 



BMCS-CJ6









## SSB System | **P6**

#### **DIRECT-TO OR BETWEEN STUDS**
























External Adj. Screws Adjustable 0" to 1-1/2"



6-way Adjustability



DIRECT-TO-STUD Guided slots on each side allow the box to

**BETWEEN STUDS** FA-SSB-UMAB Installed Between Studs

ON HARD LID FA-SSB-4R Installed in Hard Lid Ceiling Joist

#### **DROP CEILING APPLICATIONS**


be easily adjusted by external screws






**FIRE ALARM ON T-BAR** 

FA-TBAR-UMAB Installed in Drop Ceiling Grid



Tek screw provisions on each clip comply with NEC 314.23 (D) (1)





SSBT-4R & FA-TBAR-4R ON T-BAR

Shown Installed in Drop Ceiling w/ Branch Line Restraint



# Ready-to-Install Boxes & Brackets P8

## IN-STOCK, PRE-ASSEMBLED ROUGH-IN PRODUCTS

	0100	-		-			les - l		
	Cat No.	Std. Pkg	Installation Image			Cat No.	Std. Pkg	Installation Image	
	UMAB	10				UMIAB-35			
ARM	FA-UMAB  10  Adjustable 0" to 1-1/2"			FA-UMIAB-35		10 A	djustable 1/2" to 1-1/2"		
	Cat No.		Compo	nents	Std. Pkg	Installation Images			
FIRE ALARM	FA-SSB-UMAB		SSB-T5	FA-UMAB	10				
	FA-TBAR-UMAB	*	SSB-TBAR	FA-UMAB	10				
na S	FA-UMAB-4R		-	-	20				
SMOKE	FA-SSB-4R		SSB-T5	FA-UMAB-4R	20	Direct-to-Stud		irect-to-Stud	
~ <u>a</u>	FA-TBAR-4R	S	SB-TBAR	FA-UMAB-4R	20				
LIGHTING	UMAB-4R		-	-	20	in hard lid ceiling Installed  Show Stopper		stalled UMAB-4R Shown Installed on SSB-T5	
LIGH	SSBT-4R	*	SSB-TBAR	UMAB-4R	20				
MULTI-GANG	SSB-MB3 (Shown)	C	SSB-T5	MB-3	10				

See Page P2 for more Multigang Box on SSB Models





