


As a leading manufacturer of electrical products, Orbit offers one of the largest selections of electrical boxes and rings in the industry. Our state-of-the-art manufacturing facilities and industry trained engineers ensure the production and development of quality electrical products. With the contractor as our main priority, all of our boxes are cleaned, deburred and offered with a variety of brackets and knockouts to suit various applications.



BRACKET OPTIONS



Up to 7 different types

FLUSH KNOCKOUTS



Variety of options

CLEAN BOXES AND NO SHARP EDGES



Clean and deburred boxes

EMBOSS AND PIGTAIL



Reduce waste and time
10" length pigtail on select boxes

CLAMPS



Accommodates metal and
non-metallic cables

PRE-INSTALLED RAISED SCREWS




Easy installation out of box




Bracket Specification


BRACKET TYPE	AB	B (for S)	FB (for S)	FB (for FSB)	FB (for R)	FB (for H)	LB	MS	OB	WB
Length	5-7/8"	3"	7-3/8"	5-1/2"	7-1/4"	7"	2 - 3/8"	2-1/2"	6-3/4"	7-1/2"
Width	7/8"	2"	1-9/16"	2-1/8"	3/4"	1"	2 - 23/32"	1-3/8"	1-3/16"	1-9/16"
Offset	0" (Flush)	0" (Flush)	0" (Flush)	9/16"	1/2"	9/16"	1/4"	0" (Flush)	1-5/16"	0" (Flush)




"AB" 90° BRACKET
Positions box against face and side of stud.




"B" BRACKET for Square Box
Face mounts on front edge of wood stud.




"FB" BRACKET for Square Box
Mounts on flat side of stud.




"FB" BRACKET for FSB
Flush-Mounts on flat side of stud or joist.




"FB" BRACKET for Round Box
Offset Mounts on flat side of stud or joist.




"FB" BRACKET for Handy Box
Mounts on flat side of stud.




"LB" BRACKET
With spurs, slotted holes for toe-nailing.



"MS" BRACKET
Self-Gripping Metal Stud Bracket with Box Support Clip.
***Model Revised Feb. 2008**




"OB" BRACKET
Positions box away from side of stud for door frame trim clearance.




"WB" BRACKET
With positioning spurs to mount box on side of stud.


Clamp Specification




"BX/MC" Clamp
Accommodates Metal Clad Cables from size #14-2 to #10-4
****All MC series boxes are suitable for use with MCI-A Type**



"NM" Clamp
Accommodates #14-2 to #10-3 Non-Metallic Cables with ground




"NM" Clamp for Pancake Box
Accommodates #14-2 Non-Metallic Sheathed Cables with ground



"NM" Clamp for Beveled Switch Box
Accommodates #14-2 to #10-3 Non-Metallic Sheathed Cables with ground. 45° & 90° Screw Mounting.

Knockout & Pryout Specification



4" OCTAGON (40) BOXES**DRAWN****1-1/2" DEEP**

15.5 Cu. In.

NOTE

- For Fixture/Luminaire Support of 50 lbs or less

4" OCTAGON (40) BOXES & EXTENSION RINGS**WELDED****1-1/2" DEEP**


15.5 Cu. In.

BAR HANGER FEATURES


- BHA:** Adjustable Bar Hanger allows installation of box anywhere along length of stud
- 4RB-50-BHA includes 3/8" - 18 NPS trade sized stud to accommodate fixture stem

NOTE


- For Fixture/Luminaire Support of 50 lbs or less
- *For Fixture/Luminaire Support of 50 lbs or less at 16 in. Span




4RB-50-LB




4RB-50




4RB-MKO




*4RB-50-BHA




4RB-50-FB



4RB-MKO-FB




4RB-50-EXT




4RB-MKO-EXT



D4RB-50



D4RB-50/75



D4RB-75

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D4RB-50	4 - 1/2"	5 - 1/2"	50
D4RB-50/75	2 - 1/2", 2 - 3/4"	3 - 1/2", 2 - 3/4"	50
D4RB-75	4 - 3/4"	3 - 1/2", 2 - 3/4"	50

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RB-50	-	4 - 1/2"	5 - 1/2"	50
4RB-MKO	-	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	50
4RB-50-FB	FB, 1/2"	3 - 1/2"	5 - 1/2"	50
4RB-MKO-FB	FB, 1/2"	1 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	50
4RB-50-LB	LB, Flush	4 - 1/2"	5 - 1/2"	50
*4RB-50-BHA	BHA-1, Adj. 16" to 24"	4 - 1/2"	4 - 1/2"	25
4RB-50-EXT	-	4 - 1/2"	-	50
4RB-MKO-EXT	-	2 - 1/2", 2 - MKO	-	50


4" OCTAGON (40) BOXES**WELDED****1-1/2" DEEP**

15.5 Cu. In.


WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less (Except 4RB-NM-E and 4RB-NM-SG)
- *For Fixture/Luminaire Support of 50 lbs or less at 16 in. Span


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RB-NM	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-E	Ears	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-FB	FB, 1/2"	1 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-LB	LB, Flush	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-SG	Swing Bracket - Old Work	4 - Loom	1 - 1/2"	50
*4RB-NM-BHA	BHA-1, Adj. 16" to 24"	2 - 1/2", 4 - Loom	-	25




4RB-NM




4RB-NM-E




4RB-NM-FB



4RB-NM-LB



4RB-NM-SG



*4RB-NM-BHA

- 600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Visit www.ul.com or QCIT Guide on page W1 for more information