

F32 | Beam & Purlin



SPRING STEEL HAMMER ON FLANGE CLIPS BOTTOM MOUNT

PRODUCT FEATURES

- Supports boxes, fixtures or other attachments from beam flanges
- Requires only a hammer to install



Cat. No.	Flange Thickness	Hole Size	Static Load (lbs.)			Std. Pkg.
			Bottom Hole	Side Hole	Strap	
FM24	1/8" to 1/4"	1/4", Threaded	100	25	75	100
FM58	5/16" to 1/2"	1/4", Threaded	100	25	75	100
FM912	9/16" to 3/4"	1/4", Threaded	100	25	75	100

SPRING STEEL HAMMER ON FLANGE CLIPS BOTTOM MOUNT WITH STUD

PRODUCT FEATURES

- Supports boxes, fixtures or other attachments from beam flanges
- Requires only a hammer to install



Cat. No.	Flange Thickness	Hole Size	Screw Size	Static Load (lbs.)			Std. Pkg.
				Bottom Hole	Side Hole	Strap	
FM24S	1/8" to 1/4"	1/4", Threaded	1/4" X 3/8"	100	25	75	100
FM58S	5/16" to 1/2"	1/4", Threaded	1/4" X 3/8"	100	25	75	100
FM912S	9/16" to 3/4"	1/4", Threaded	1/4" X 3/8"	100	25	75	100

SPRING STEEL HAMMER ON FLANGE CLIPS SIDE MOUNT

PRODUCT FEATURES

- Provides attachment for wire, S-hooks, chain to flanges
- Fits most beams
- Requires only a hammer to install



Cat. No.	Flange Thickness	Hole Size	Static Load (lbs.)	Std. Pkg.
F2H4	3/32" to 9/64"	1/4", Plain	160	100
F4H24	1/8" to 1/4"	1/4", Plain	200	100
F4H58	5/16" to 1/2"	1/4", Plain	200	100
F4H912	9/16" to 3/4"	1/4", Plain	200	100

SPRING STEEL ROD TO FLANGE CLIPS

PRODUCT FEATURES

- Provides attachment for threaded rod to flanges
- Can swivel to provide a vertical dropdown
- Requires only a hammer to install



Cat. No.	Flange Thickness	Hole Size	Static Load (lbs.)	Std. Pkg.
F4TI24	1/18" to 1/4"	1/4", Threaded	200	100
F4TI58	5/16" to 1/2"	1/4", Threaded	200	100
F4TI912	9/16" to 3/4"	1/4", Threaded	200	100