

Orbit carries an extensive variety of Fastening and Support products for electrical and datacom installations. Many of Orbit's Fasteners are composed of Spring Steel material, which are incredibly versatile, and often require no tools to install. Orbit constantly evaluates its product mix to ensure contractors have access to the products they need. Our vast Fastener and Support selection includes Spring Steel Cable & Conduit Clips, Wall Mounted Box Brackets, Ceiling Hangers & Plates, Datacom Support Products, and more.



# MATERIALS SPRING STEEL & SHEET STEEL Spring Steel Orbit's Fasteners are available in a variety of sizes and two basic steel materials.



# F32 | Beam & Purlin



# SPRING STEEL HAMMER ON FLANGE CLIPS BOTTOM MOUNT

### **PRODUCT FEATURES**

- Supports boxes, fixtures or other attachments from beam flanges
- Requires only a hammer to install

	Flange	Hole	Static Load (lbs.)		.)	Std.
Cat. No.	Thickness	Size	<b>Bottom Hole</b>	Side Hole	Strap	Pkg.
FM24	1/8" to 1/4"	1/4", Threaded	100	25	75	100
FM58	5/16" to 1/2"	1/4", Threaded	100	25	75	100
FM912	9/16" to 3/4"	1/4", Threaded	100	25	75	100





# SPRING STEEL HAMMER ON FLANGE CLIPS BOTTOM MOUNT WITH STUD

### **PRODUCT FEATURES**

- Supports boxes, fixtures or other attachments from beam flanges
- Requires only a hammer to install

	Flange	Hole	Screw	Static Load (lbs.)			Std.
Cat. No.	Thickness	Size	Size	<b>Bottom Hole</b>	Side Hole	Strap	Pkg.
FM24S	1/8" to 1/4"	1/4", Threaded	1/4" X 3/8"	100	25	75	100
FM58S	5/16" to 1/2"	1/4", Threaded	1/4" X 3/8"	100	25	75	100
FM912S	9/16" to 3/4"	1/4", Threaded	1/4" X 3/8"	100	25	75	100





# SPRING STEEL HAMMER ON FLANGE CLIPS SIDE MOUNT

### PRODUCT FEATURES

- Provides attachment for wire, S-hooks, chain to flanges
- Fits most beams
- Requires only a hammer to install

Cat. No.	Flange Thickness	Hole Size	Static Load (lbs.)	Std. Pkg.
F2H4	3/32" to 9/64"	1/4", Plain	160	100
F4H24	1/8" to 1/4"	1/4", Plain	200	100
F4H58	5/16" to 1/2"	1/4", Plain	200	100
F4H912	9/16" to 3/4"	1/4", Plain	200	100







## SPRING STEEL ROD TO FLANGE CLIPS

### **PRODUCT FEATURES**

- Provides attachment for threaded rod to flanges
- Can swivel to provide a vertical dropdown
- Requires only a hammer to install

Cat. No.	Flange Thickness	Hole Size	Static Load (lbs.)	Std. Pkg.
F4TI24	1/18" to 1/4"	1/4", Threaded	200	100
F4TI58	5/16" to 1/2"	1/4", Threaded	200	100
F4TI912	9/16" to 3/4"	1/4", Threaded	200	100

F4H58

F4H912





