

# H9 | LED High Bays

## LUHB4 SERIES

### PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Black Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 1/2" heavy-duty Fixture Hook Included
- ▶ Ambient Operating Temp: -40°C / -40°F to 50°C / 122°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage Models (120~277V 150W/300W)
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

### CERTIFICATES



120~277V



277V~480V



Adjustable Wattage DIP switch on 150W, 300W 120~277V

| Catalog No.        | Voltage  | System Wattage         | Color Temp. | Lumens                                     | Wattage Equiv.            |
|--------------------|----------|------------------------|-------------|--------------------------------------------|---------------------------|
| *LUHB4-100W-CW     | 120~277V | 100W                   | 5000K       | 15,000 lm                                  | 400W MH                   |
| *LUHB4-150W-CW     |          | 50W/ 80W/ 100W/ 150W   |             | 7,400 lm/ 11,840 lm/ 14,800 lm/ 22,200 lm  | 175W/ 250W/ 400W/ 750W MH |
| *LUHB4-230W-CW     |          | 230W                   |             | 33,350 lm                                  | 1,000W MH                 |
| LUHB4-300W-CW      |          | 150W/ 200W/ 240W/ 300W |             | 21,000 lm/ 28,000 lm/ 33,600 lm/ 42,000 lm | 750W/ 1,000W MH           |
| LUHB4-230W-CW-480V | 277~480V | 230W                   |             | 32,890 lm                                  | 1,000W MH                 |
| LUHB4-300W-CW-480V |          | 300W                   |             | 42,900 lm                                  | 1,000W MH                 |

## ACCESSORIES Sold Separately



\*LUHB4-T-100 (For 100W-150W)  
LUHB4-T-230 (For 230W-300W)

## NEW AWC-LUHB5 SERIES

### PRODUCT FEATURES


- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ Black Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 1/2" heavy-duty Fixture Hook Included
- ▶ Ambient Operating Temp: -40°C / -40°F to 50°C / 122°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage & CCT
- ▶ 0-10V Dimmable
- ▶ 5 Year Limited Warranty

### CERTIFICATES



Wattage Adjustment Switch

CCT Adjustment Switch



Motion Sensor Optional

| Catalog No.                                 | Voltage      | System Wattage   | Color Temp.               | Lumens                          | Wattage Equiv.  |
|---------------------------------------------|--------------|------------------|---------------------------|---------------------------------|-----------------|
| AWC-LUHB5-150W                              | 120~<br>277V | 100W/ 120W/ 150W | 3500K/<br>4000K/<br>5000K | 13,451 lm/ 16,141 lm/ 20,176 lm | 400W/ 750W MH   |
| AWC-LUHB5-240W                              |              | 180W/ 200W/ 240W |                           | 24,274 lm/ 26,971 lm/ 32,365 lm | 750W/ 1,000W MH |
| Single Wattage and Single Color Temperature |              |                  |                           |                                 |                 |
| LUHB5-150W-CW                               | 120~277V     | 150W             | 5000K                     | 20,421 lm                       | 750W MH         |

## ACCESSORIES Sold Separately



DMS1



DMS1-RC



LUHB5-T-150 (For 150W)  
LUHB5-T-240 (For 240W)

SCAN FOR MORE INFO

