

## Transformer Lug Kits

### Type LASK

- Kits contain Type LA aluminum dual rated lugs, steel nuts and bolts
- Available in four sizes and can be used with any dry-type transformer
- Plated steel hardware for corrosion resistance
- Nuts have special captive conical pressure washers that maintain bolted contact pressure when properly torqued
- Each lug is clearly marked "AL9CU"
- Rated for 600 V, 90°C applications
- The use of oxide inhibitor is recommended for all aluminum terminations



| CATALOG NUMBER | TRANSFORMER KVA SIZE                | KIT CONTENTS |        |                    |      |                         |
|----------------|-------------------------------------|--------------|--------|--------------------|------|-------------------------|
|                |                                     | QTY.         | LUGS   | CONDUCTOR RANGE    | QTY. | HARDWARE                |
| LASK-1         | 15-37 1/2 1-Phase<br>15-45 3-Phase  | 8            | LA-2   | 14 Str. - 2 Str.   | 8    | 1/4 - 20 x 3/4" Bolts   |
|                |                                     | 4            | LA-250 | 6 Str. - 250 kcmil | 8    | 1/4 - 20 Flange Nuts    |
| LASK-2         | 50-75 1-Phase<br>75-112 1/2 3-Phase | 12           | LA-250 | 6 Str. - 250 kcmil | 8    | 1/4 - 20 x 3/4" Bolts   |
|                |                                     |              |        |                    | 8    | 1/4 - 20 x 1 3/4" Bolts |
|                |                                     |              |        |                    | 16   | 1/4 - 20 Flange Nuts    |
| LASK-3         | 100-167 1-Phase<br>150-300 3-Phase  | 3            | LA-250 | 6 Str. - 250 kcmil | 3    | 1/4 - 20 x 3/4" Bolts   |
|                |                                     | 22           | LA-600 | 2 Str. - 600 kcmil | 3    | 1/4 - 20 Flange Nuts    |
|                |                                     |              |        |                    | 16   | 3/8 - 16 x 2" Bolts     |
| LASK-4         | 500 3-Phase                         | 29           | LA-600 | 2 Str. - 600 kcmil | 16   | 3/8 - 16 Flange Nuts    |
|                |                                     |              |        |                    | 18   | 3/8 - 16 x 2" Bolts     |
|                |                                     |              |        |                    | 18   | 3/8 - 16 Flange Nuts    |