

Bronze Ground Clamps for Rigid Conduit with 360° Swivel Hub

Type KL

- Cast from high strength, high conductivity copper alloy
- Designed to connect copper grounding conductor in rigid or intermediate metal conduit (IMC) to galvanized steel or copper water pipe
- Integral clamp swivels 360° and allows for easy alignment
- Standards: UL 467, CSA C22.2NO.41

CATALOG NUMBER	FIG. NO.	WATER PIPE RANGE	CONDUCTOR RANGE	CONDUIT HUB SIZE	SCREW MATERIAL
KL-0	1	1/2" - 1"	10 Sol. - 6 Str.	1/2"	Zinc Plated Steel
KL-1	2		10 Sol. - 2/0 Str.	3/4"	
KL-1A	2		10 Sol. - 3/0 Str.	1"	
KL-20	1	1 1/4" - 2"	10 Sol. - 6 Str.	1/2"	
KL-2	2		10 Sol. - 2/0 Str.	3/4"	
KL-2A	2		10 Sol. - 3/0 Str.	1"	
KL-40	1	2 1/2" - 4"	10 Sol. - 6 Str.	1/2"	
KL-4	2		10 Sol. - 2/0 Str.	3/4"	
KL-4A	2		10 Sol. - 3/0 Str.	1"	

Fig. 1



Fig. 2

Bronze Ground Clamps for Rigid Conduit, IMC, or EMT with 360° Swivel Hub

Type KS

- Cast from high strength, high conductivity copper alloy
- Designed to connect copper grounding conductor in rigid conduit, intermediate metal conduit (IMC), or EMT to galvanized steel or copper water pipe
- Integral hub accommodates rigid, IMC, or EMT conduit and swivels 360° for easy alignment
- Standards: UL 467, CSA C22.2NO.41

CATALOG NUMBER	WATER PIPE RANGE	CONDUCTOR RANGE	RIGID & IMC CONDUIT SIZE	EMT CONDUIT SIZE	SCREW MATERIAL
KS-1	1/2" - 1"	10 Sol. - 6 Str.	1/2"	3/4"	Zinc Plated Steel
KS-2	1 1/4" - 2"				
KS-4	2 1/2" - 4"				

