

Bronze Conduit Hubs with 360° Swivel

Type KLH

- Cast from high strength, high conductivity copper alloy
- Designed to be used with bronze grounding pipe clamps to connect rigid conduit to water pipe for grounding applications
- Hub swivels 360° for easy alignment
- Standards: UL 467, CSA C22.2NO.41

CATALOG NUMBER	FIG. NO.	CONDUIT SIZE	CONDUCTOR RANGE	SCREW MATERIAL
KLH-12	1	1/2"	10 Sol. - 6 Str.	Zinc Plated Steel
KLH-34	2	3/4"	10 Sol. - 2/0 Str.	
KLH-1	2	1"	10 Sol. - 3/0 Str.	



Aluminum Dual Rated Ground Clamps

Type GC

- Manufactured from high strength aluminum alloy
- Designed to connect aluminum or copper ground conductors to copper water pipe, galvanized pipe, or steel conduit
- Clear plated for corrosion protection and low contact resistance
- Standards: UL 467

CATALOG NUMBER	WATER PIPE RANGE	CONDUCTOR RANGE	CLAMP SCREW MATERIAL	CONDUCTOR GROOVE SCREW MATERIAL
GC-1	1/2" - 1"	14 Sol. - 1/0 Str.	Zinc Plated Steel	Tin Plated Aluminum
GC-2	1 1/4" - 2"	6 Sol. - 250 kcmil		
GC-4	2 1/2" - 4"	6 Sol. - 250 kcmil		

