


Cast Copper Tanker Static Ground Clamp

Type TSGC

- Manufactured from high strength cast copper alloy
- Ribbed design provides multiple contacts with the tank car
- Pointed wing screw design penetrates surface finishes to ensure a positive grounding contact
- Accommodates flexible rubber sheathed cable

CATALOG NUMBER	COPPER CONDUCTOR RANGE	HEX SIZE
TSGC-030	#6 - #2 AWG	3/8




Bronze Ground Rod Clamps

Types CAB and CEB

- Manufactured from corrosion resistant cast aluminum bronze
- Designed to join a range of cable to copper clad, galvanized steel and stainless steel ground rods
- Slips over end of rod for single wrench installation
- Furnished with silicon bronze hex head bolt
- UL listed for direct burial in earth and concrete
- Socket head screws can be furnished by suffixing catalog number with "-S"
- For tin plating, suffix catalog number with "-TN"



Type CEB-U



Type CAB



Type CEB



Type CAB-M



Heavy Duty Clamps

CATALOG NUMBER	ACCOMMODATES ROD SIZE (IN.)	CONDUCTOR RANGE
CAB-1M	1/2	10 Sol. - 2 Str.
CAB-2M*	5/8	8 Sol. - 1/0 Str.
CAB-3M	3/4	8 Sol. - 1/0 Str.

Standard Clamps

CATALOG NUMBER	ACCOMMODATES ROD SIZE (IN.)	CONDUCTOR RANGE
CAB-0	3/8	14 Sol. - 6 Str.
CAB-1	1/2	10 Sol. - 2 Str.
CAB-2	5/8	8 Sol. - 1/0 Str.
CAB-3	3/4	8 Sol. - 1/0 Str.
CAB-4	3/4	4/0 Str.
CAB-5	1	8 Sol. - 1/0 Str.
CAB-6	1	4/0 Str.

Economy Clamps

CATALOG NUMBER	ACCOMMODATES ROD SIZE (IN.)	CONDUCTOR RANGE
CEB-1+	1/2	8 Sol. - 2 Str.
CEB-2+	5/8	8 Sol. - 2 Str.
CEB-3+	3/4	8 Sol. - 2 Str.

Universal Ground Rod Clamp

CATALOG NUMBER	ACCOMMODATES ROD SIZES (IN.)	CONDUCTOR RANGE
CEB-U	1/2, 5/8, and 3/4	10 Sol. - 1/0 Str.

* For 1/2" thread bolt and extra long body, use CAB-2ML

+ RUS accepted plain and tin plated

• RUS accepted tin plated only