



Bronze Ground Clamp Connectors

Type GR

- Manufactured from high copper content alloy
- Used to connect three equal size cables to rod, water pipe, or structured tube
- Furnished with silicon bronze bolt, nuts, and lockwashers for corrosion resistance
- Suitable for direct burial in earth or concrete
- Single wrench installation
- UL 467 listed



CATALOG NUMBER	ACCOMMODATES		CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)				BOLT SIZE
	ROD	IPS		A	B	C	D	
GR-1	1/2	1/4	8 Sol. - 4 Str.	2.50	1.50	2.25	1.00	3/8
GR-2			4 Sol. - 2/0 Str.	3.00	1.50	2.50	1.00	3/8
GR-3			2/0 Sol. - 250 kcmil	3.63	1.50	2.75	1.00	3/8
GR-4	5/8 or 3/4	3/8	8 Sol. - 4 Str.	2.75	1.50	2.50	1.13	3/8
GR-5			4 Sol. - 2/0 Str.	3.00	1.50	2.75	1.13	3/8
GR-6			2/0 Sol. - 250 kcmil	3.50	1.63	3.00	1.13	3/8
GR-7 •			300 - 500 kcmil	4.00	1.63	3.25	1.13	1/2
GR-8	7/8 or 1	1/2 or 3/4	8 Sol. - 4 Str.	2.88	1.50	3.00	1.50	3/8
GR-9			4 Sol. - 2/0 Str.	3.50	1.50	3.25	1.50	3/8
GR-10			2/0 Sol. - 250 kcmil	3.88	1.63	3.38	1.50	1/2
GR-11 •			300 - 500 kcmil	4.38	1.63	3.50	1.50	1/2
GR-12 •			500 - 750 kcmil	5.00	1.75	4.00	1.63	1/2
GR-13	-	1	8 Sol. - 4 Str.	3.25	1.50	3.00	1.75	3/8
GR-14			4 Sol. - 2/0 Str.	3.63	1.50	3.25	1.75	3/8
GR-15			2/0 Sol. - 250 kcmil	4.13	1.63	3.50	1.75	3/8
GR-16 •			300 - 500 kcmil	4.50	1.63	3.75	1.75	1/2
GR-17 •			500 - 750 kcmil	5.13	1.75	4.25	1.88	1/2
GR-18 •			750 - 1000 kcmil	5.50	1.75	4.50	1.88	1/2
GR-19	-	1 1/4	8 Sol. - 4 Str.	3.50	1.50	3.50	2.06	3/8
GR-20			4 Sol. - 2/0 Str.	4.00	1.50	3.75	2.06	3/8
GR-21			2/0 Sol. - 250 kcmil	4.50	1.63	3.88	2.06	3/8
GR-22 •			300 - 500 kcmil	5.13	1.75	4.38	2.19	1/2
GR-23 •			500 - 750 kcmil	5.75	2.00	5.13	2.31	5/8
GR-24 •	-	1 1/2	750 - 1000 kcmil	6.25	2.00	5.38	2.31	5/8
GR-25			8 Sol. - 4 Str.	3.75	1.50	3.75	2.38	3/8
GR-26			4 Sol. - 2/0 Str.	4.25	1.50	4.00	2.38	3/8
GR-27			2/0 Sol. - 250 kcmil	4.75	1.75	4.25	2.38	3/8
GR-28 •			300 - 500 kcmil	5.50	2.00	4.75	2.50	1/2
GR-29 •			500 - 750 kcmil	6.25	2.25	5.25	2.63	5/8
GR-30 •			750 - 1000 kcmil	6.50	2.25	5.50	2.63	5/8



• UL listing is limited to maximum wire size of 250 kcmil