

Vise Style Parallel Connectors


Type FF

- Body and clamp are manufactured from high strength bronze alloy
- Silicon bronze washer head bolt
- Designed to be used as a copper to copper grounding splice or tap connection in utility, telecom, CATV, and residential applications
- Non-swiveling design with full thread engagement
- UL 467 listed



CATALOG NUMBER	CONDUCTOR RANGE		APPROXIMATE DIMENSIONS (IN.)			BOLT SIZE	HEX SIZE ACROSS FLATS
	MAXIMUM 2 CONDUCTORS	MINIMUM 2 CONDUCTORS	D	H	W		
FF-6*	6 Sol.	8 Sol.	.75	1.00	.63	1/4 - 28	3/8
FF-4	4 Str.	6 Sol.	.81	1.16	.63	5/16 - 24	9/16
FF-2	2 Str.	4 Sol.	.81	1.38	.81	5/16 - 24	9/16
FF-2/0	2/0 Str.	2 Sol.	1.13	1.88	.97	3/8 - 24	9/16
FF-4/0	4/0 Str.	1/0 Sol.	1.19	2.13	.94	3/8 - 24	9/16

* Supplied with slotted hex head bolts only



Insulation Piercing Vise Style Parallel Connectors

Type MGC

- Manufactured from high strength bronze alloy
- Designed for use on self-supporting Rural, Figure 8, or IM type telephone cable to connect the messenger to the ground wire
- Tin plated for maximum conductivity and corrosion resistance
- Stainless steel bolt for corrosion resistance
- Insulation piercing teeth eliminate the need for wire stripping



CATALOG NUMBER	CONDUCTOR RANGE		APPROXIMATE DIMENSIONS (IN.)			BOLT SIZE
	MESSENGER CABLE SIZE	TAP	A	B	C	
MGC-167	.146" - .312"	8 Str. - 4 Str. (.146" - .232" dia.)	1.63	1.25	1.00	5/16-18 1/2 HEX
MGC-167 9/16	.146" - .312"	8 Str. - 4 Str. (.146" - .232" dia.)				5/16-24 9/16 HEX

