

Aluminum Wide Range Double Tab Press-Ons

Types KO-R and KD-R

- Manufactured from high conductivity aluminum
- Designed for overhead line tap applications with copper*, aluminum, ACSR, and compact conductors
- In copper to aluminum applications, H-shaped profile with solid barrier provides conductor separation, prevents strand cutting, and minimizes galvanic corrosion
- Deep indent crimp lines make crimp location clearly visible
- Bendable tabs secure both run and tap conductors, enabling the user to easily operate installation tool
- Pre-filled with oxide inhibitor and individually boxed



*Note: Not recommended for copper to copper applications

7 Connector Program - Mechanical or Hydraulic Tool

CATALOG NUMBER	PROGRAM NUMBER	GROOVE	STANDARD CONDUCTOR			COMPACT CONDUCTOR		NO. OF CRIMPS		DIE SIZE
			ACSR & ALUMINUM ALLOY	AL OR CU STRANDED	AL OR CU SOLID	ACSR	STRANDED	MECH. TOOL	HYD. TOOL	
KO-R06	1	A B	6, 4, 2, 6/1 6, 4, 2, 6/1	6, 4, 3-7, 2 6, 4, 3-7, 3	6, 4, 3, 2 6, 4, 3, 2	6, 4, 3, 2 6, 4, 3, 2	6, 4, 3, 2, 6, 4, 3, 2,	4	2	0
KO-R08	2	A B	3, 2, 1, 1/0 6, 4, 3, 2,	3-3, 2, 1/0, 2/0 6, 4, 3, 2, 1-19	1, 1/0, 2/0 6, 4, 3, 2, 1, 1/0	2, 1, 1/0 6, 4, 3, 2, 1	2, 1, 1/0, 2/0 6, 4, 3, 2, 1	5	2	0
KD-R02	3	A B	1/0, 2/0 6, 4, 3, 2	2/0, 3/0 6, 4, 3, 2, 1-19	3/0, 4/0, 6, 4, 3, 2, 1, 1/0	2/0, 3/0 6, 4, 3, 2, 1	3/0 6, 4, 3, 2, 1	4	2	D
KD-R04	4	A B	1, 1/0, 2/0 1, 1/0, 2/0	1-3, 1/0, 2/0, 3/0 1-3, 1/0, 2/0	2/0, 3/0, 4/0 2/0, 3/0	1/0, 2/0, 3/0 1/0, 2/0, 3/0	1/0, 2/0, 3/0 1/0, 2/0, 3/0	5	2	D
KD-R03	5	A B	3/0, 4/0 6, 4, 3, 2	4/0 6, 4, 3, 2, 1-19	250, 266, 300 6, 4, 3, 2, 1, 1/0	4/0, 266 18/1 6, 4, 3, 2, 1	4/0, 250, 266 6, 4, 3, 2, 1	4	2	D
KD-R05	6	A B	3/0, 4/0 1, 1/0, 2/0	3/0, 4/0 1-3, 1/0, 2/0	2/0, 3/0	3/0, 4/0, 266 18/1 1/0, 2/0	4/0, 250, 266 1/0, 2/0, 3/0	7	3	D
KD-R28	7	A B	3/0, 4/0 3/0, 4/0	3/0, 4/0 3/0, 4/0	-	3/0, 4/0, 266 18/1 3/0, 4/0, 266 18/1	4/0, 250, 266 4/0, 250, 266	7	3	D
KO-R10	-	A B	4, 3, 2, 1, 1/0 4, 3, 2, 1, 1/0	4, 3, 2, 1, 1/0, 2/0 4, 3, 2, 1, 1/0, 2/0	2, 1, 1/0 2, 1, 1/0	4, 3, 2, 1, 1/0 4, 3, 2, 1, 1/0	4, 3, 2, 1, 1/0, 2/0 4, 3, 2, 1, 1/0, 2/0	5	2	0
KO-R33	-	A B	6, 4 6, 4	6, 4, 3-7 6, 4, 3-7	6, 4, 3, 2 6, 4, 3, 2	6, 4, 3 6, 4, 3	6, 4 6, 4	4	2	0

4 Connector Program - Hydraulic Tool Only

CATALOG NUMBER	GROOVE	STANDARD CONDUCTOR			COMPACT CONDUCTOR		NO. OF CRIMPS (HYD. TOOL)	DIE SIZE
		ACSR & AL ALLOY	AL OR CU STRANDED	AL OR CU SOLID	ACSR	STRANDED		
KO-R01	A B	6, 4, 3, 2, 1, 1/0 6, 4, 3, 2	6, 4, 3, 2, 1, 1/0 6, 4, 3, 2, 1-19	6, 4, 3, 2, 1, 1/0 6, 4, 3, 2, 1, 1/0	6, 4, 3, 2, 1, 1/0 6, 4, 3, 2, 1	6, 4, 3, 2, 1, 1/0 6, 4, 3, 2, 1	2	0
KD-R03	A B	1, 1/0, 2/0, 3/0, 4/0 6, 4, 3, 2	1-3, 1/0, 2/0, 3/0, 4/0 6, 4, 3, 2, 1-19	2/0, 3/0, 4/0 6, 4, 3, 2, 1/0	1/0, 2/0, 3/0, 4/0, 266 18/1, 6, 4, 3, 2, 1	1/0, 2/0, 3/0, 4/0, 250, 266 6, 4, 3, 2, 1	2	D
KD-R05	A B	1, 1/0, 2/0, 3/0, 4/0 1, 1/0, 2/0	1-3, 1/0, 2/0, 3/0, 4/0 1-3, 1/0, 2/0	2/0, 3/0, 4/0 2/0, 3/0	1/0, 2/0, 3/0, 4/0, 266 18/1 1/0, 2/0	1/0, 2/0, 3/0, 4/0, 250, 266 1/0, 2/0, 3/0	3	D
KD-R28	A B	2/0, 3/0, 4/0 2/0, 3/0, 4/0	3/0, 4/0 3/0, 4/0	-	3/0, 4/0, 266 18/1 3/0, 4/0, 266 18/1	3/0, 4/0, 250, 266 3/0, 4/0, 250, 266	3	D