



Aluminum Service Entrance Sleeves

Type PS

.840" OD



- Forged from pure aluminum with integral solid center barrier
- For combinations of copper, aluminum, and ACSR
- Designed for service entrance and non-tension loop splice applications
- Solid center barrier allows for proper conductor insertion and eliminates the effects of galvanic corrosion in aluminum to copper connections
- Installed with standard dies in either hand or hydraulic tools
- Easy push-thru polyethylene color coded caps seal out contaminants
- Connectors are pre-filled with oxide inhibitor to keep air and moisture out
- Conforms to ANSI C 119.4 when properly installed



CATALOG NUMBER	A RANGE			B RANGE				NO. OF CRIMPS EACH END		DIE SIZE
	ACSR	AL OR CU STRANDED	CAP COLOR	ACSR	AL OR CU STRANDED	AL OR CU SOLID	CAP COLOR	HAND	HYD.	
PS-00	1/0	1/0	Yellow	1/0	1/0	-	Yellow	7	4	.840, 249
PS-202	2/0	2/0	Gray	4	3-4	2	Orange			
PS-201				2	1-2	1/0	Red			
PS-200				1/0	1/0	-	Yellow			
PS-2020				2/0	2/0	-	Gray			
PS-302	3/0	3/0	Black	4	3-4	2	Orange			
PS-301				2	1-2	1/0	Red			
PS-300				1/0	1/0	-	Yellow			
PS-3020				2/0	2/0	-	Gray			
PS-3030				3/0	3/0	-	Black			
PS-402	4/0	4/0	Pink	4	3-4	2	Orange			
PS-401				2	1-2	1/0	Red			
PS-400				1/0	1/0	-	Yellow			
PS-4020				2/0	2/0	-	Gray			
PS-4030				3/0	3/0	-	Black			
PS-4040				4/0	4/0	-	Pink			