


Underground Compression Terminal Kits

Type DBTBF

- Kit is designed to be used in conjunction with Underground Multi-Tap Connectors (Type DBA)
- Consists of an aluminum compression lug, hex head cap screw with captive conical pressure washer, and a pre-lubricated force-fit rubber sleeve
- Upon completion of crimp, bolt connector to Type DBA bar and slide force-fit sleeve over joint to obtain a water-tight connection



CATALOG NUMBER	CONDUCTOR RANGE		DIE SIZE	INSTALLATION TOOLS & DIES (NO. OF CRIMPS)	
	COPPER	ALUMINUM		TMU-0D3 (MECH. TOOL) WITH "W" DIES	TPU-12B (HYD. TOOL) WITH "U" DIES
DBTBF-C6	6 Str. - 4 Sol.	6 Str. - 4 Sol. 6 Str. Compact	BG, 5/8, 243, EEI 8A	BG (3), 243 (2)	BG (1), 243 (1)
DBTBF-W2	2 Sol. - 4 Str.	2 Sol. - 4 Str. 4 Str. Compact			
DBTBF-C1	2 Str. - 1/0 Sol.	2 Str. - 1/0 Sol. 2 - 1 Str. Compact			
DBTBF-010A	1/0 Str.	1/0 Str. - 2/0 Sol. 1/0 Str. Compact			
DBTBF-013	2/0 Str.	2/0 Str. - 3/0 Sol. 2/0 Str. Compact	249, 840, EEI 11A	249 (3), K840 (5)	249 (*2), K840 (3)
DBTBF-017	3/0 Str.	3/0 Str. - 4/0 Sol. 3/0 Str. Compact			
DBTBF-025	4/0 Str.	4/0 Str. - 250 kcmil 4/0 - 250 Compact			
DBTBF-030	250 kcmil	250 - 300 kcmil 300 Compact	299, 655, 750, EEI 13A	-	299 (2), 655 (3), 705 (2)
DBTBF-035	-	300 - 350 kcmil 350 Compact			

*Overlap compressions