


Bronze Stud Connectors


Type CSR-2

For stud to two cables or two tubes vertical or horizontal take offs

- Manufactured from high strength copper alloy
- Furnished with silicon bronze bolts, nuts, and lockwashers for corrosion resistance
- Caps on tap end can be rotated to utilize two grooves which accommodate a wide range of cable and IPS conductor sizes
- The reversible caps can be rotated 90° to provide straight or horizontal take offs
- Captive bolt design permits single wrench installation
- For tin plating, suffix catalog number with "-TN"



CATALOG NUMBER	A STUD THREAD SIZE	B COPPER CONDUCTOR RANGE		
		IPS RANGE	SMALL GROOVE RANGE	LARGE GROOVE RANGE
CSR-0716-050-2	3/4-16	3/8 - 1/2	6 Sol. - 4/0 Str.	4/0 Str. - 500 kcmil
CSR-0716-100-2		3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-1014-050-2	1-14	3/8 - 1/2	6 Sol. - 4/0 Str.	4/0 Str. - 500 kcmil
CSR-1014-100-2		3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-1112-050-2	1 1/8-12	3/8 - 1/2	6 Sol. - 4/0 Str.	4/0 Str. - 500 kcmil
CSR-1112-100-2		3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-1212-100-2	1 1/4-12	3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-1512-050-2	1 1/2-12	3/8 - 1/2	6 Sol. - 4/0 Str.	4/0 Str. - 500 kcmil
CSR-1512-100-2		3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-1512-200-2		3/8 - 1 1/4	4/0 Str. - 900 kcmil	900 - 2000 kcmil
CSR-2012-100-2	2-12	3/8 - 3/4	2 Sol. - 350 kcmil	350 - 1000 kcmil
CSR-2012-200-2		3/8 - 1 1/4	4/0 Str. - 900 kcmil	900 - 2000 kcmil
CSR-2512-200-2	2 1/2-12	3/8 - 1 1/4	4/0 Str. - 900 kcmil	900 - 2000 kcmil
CSR-3012-200-2	3-12	3/8 - 1 1/4	4/0 Str. - 900 kcmil	900 - 2000 kcmil



CATALOG NUMBER	APPROXIMATE DIMENSIONS (IN.)				BOLT SIZE	
	C	E	L	M	STUD	TAP
CSR-0716-050-2	1.38	2.13	4.38	1.75	3/8	3/8
CSR-0716-100-2	1.88	2.88	5.63	2.25	1/2	1/2
CSR-1014-050-2	1.38	2.88	4.38	1.75	3/8	3/8
CSR-1014-100-2	1.88	2.88	5.63	2.25	1/2	1/2
CSR-1112-050-2	1.38	2.13	5.00	2.25	3/8	3/8
CSR-1112-100-2	1.88	2.88	5.75	2.25	1/2	1/2
CSR-1212-100-2	1.88	2.88	5.75	2.25	1/2	1/2
CSR-1512-050-2	1.38	2.13	5.00	2.25	1/2	3/8
CSR-1512-100-2	1.88	2.88	5.75	2.25	1/2	1/2
CSR-1512-200-2	2.38	3.38	6.13	2.25	1/2	1/2
CSR-2012-100-2	1.88	2.88	5.75	2.75	1/2	1/2
CSR-2012-200-2	2.38	3.38	6.38	2.75	1/2	1/2
CSR-2512-200-2	2.38	3.38	6.38	2.75	1/2	1/2
CSR-3012-200-2	2.38	3.38	6.75	2.75	1/2	1/2