


Bronze Tee Connectors

Types ABR and ABRE



For tube range to cable range

- Manufactured from high strength cast copper alloy
- Furnished with silicon bronze bolts, nuts, and lockwashers for corrosion resistance
- Cap on tap end can be rotated to utilize two grooves which accommodate a wide range of cable conductor sizes
- Captive bolt design permits single wrench installation
- For tin plating, suffix catalog number with "-TN"



Four Bolt Clamping

CATALOG NUMBER	IPS RANGE (MAIN)	COPPER CONDUCTOR RANGE (TAP)	APPROXIMATE DIMENSIONS (IN.)			BOLT SIZE
			L	M	N	
ABR-10-025	3/8-1	6 Sol. - 250 kcmil	5.56	2.25	2.50	1/2
ABR-10-050		1/0 Sol. - 500 kcmil	5.56	2.25	2.50	
ABR-10-100		4/0 Sol. - 1000 kcmil	6.06	2.25	3.00	
ABR-10-200		500 - 2000 kcmil	6.06	2.25	3.00	
ABR-12-025	1 1/4	6 Sol. - 250 kcmil	6.00	2.75	2.50	
ABR-12-050		1/0 Sol. - 500 kcmil	6.00	2.75	2.50	
ABR-12-100		4/0 Sol. - 1000 kcmil	6.50	2.75	3.00	
ABR-12-200		500 - 2000 kcmil	6.50	2.75	3.00	
ABR-15-025	1 1/2	6 Sol. - 250 kcmil	6.75	2.75	2.50	
ABR-15-050		1/0 Sol. - 500 kcmil	6.75	2.75	2.50	
ABR-15-100		4/0 Sol. - 1000 kcmil	7.25	2.75	3.00	
ABR-15-200		500 - 2000 kcmil	7.25	2.75	3.00	
ABR-20-025	2	6 Sol. - 250 kcmil	7.19	2.75	2.50	
ABR-20-050		1/0 Sol. - 500 kcmil	7.19	2.75	2.50	
ABR-20-100		4/0 Sol. - 1000 kcmil	7.69	2.75	3.00	
ABR-20-200		500 - 2000 kcmil	7.69	2.75	3.00	
ABR-25-025	2 1/2	6 Sol. - 250 kcmil	7.69	2.75	2.50	
ABR-25-050		1/0 Sol. - 500 kcmil	7.69	2.75	2.50	
ABR-25-100		4/0 Sol. - 1000 kcmil	8.19	2.75	3.00	
ABR-25-200		500 - 2000 kcmil	8.19	2.75	3.00	
ABR-30-025	3	6 Sol. - 250 kcmil	8.38	3.25	2.50	
ABR-30-050		1/0 Sol. - 500 kcmil	8.38	3.25	2.50	
ABR-30-100		4/0 Sol. - 1000 kcmil	8.88	3.25	3.00	
ABR-30-200		500 - 2000 kcmil	8.88	3.25	3.00	



Two Bolt Clamping

CATALOG NUMBER	IPS RANGE (MAIN)	COPPER CONDUCTOR RANGE (TAP)	APPROXIMATE DIMENSIONS (IN.)			BOLT SIZE
			L	M	N	
ABRE-10-025	3/8-1	6 Sol. - 250 kcmil	4.13	1.50	1.50	3/8