



Bronze Couplers

Type BDR

For copper tube to copper cable

- Manufactured from high strength cast copper alloy
- Furnished with silicon bronze bolts, nuts, and lockwashers for corrosion resistance
- Cap on tap end can be reversed to accommodate a wide range of conductor sizes
- Captive bolt design permits single wrench installation
- For tin plating, suffix catalog number with "-TN"



CATALOG NUMBER	A IPS SIZE (MAIN)	B CONDUCTOR RANGE (TAP)	APPROXIMATE DIMENSIONS (IN.)			BOLT SIZE
			L	M	N	
BDR-20-025	2	6 Sol. - 250 kcmil	5.63	2.75	2.50	1/2
BDR-20-050		1/0 Sol. - 500 kcmil	5.63	2.75	2.50	
BDR-20-100		4/0 Sol. - 1000 kcmil	6.13	2.75	3.00	
BDR-20-200		500 - 2000 kcmil	6.13	2.75	3.00	
BDR-25-025	2 1/2	6 Sol. - 250 kcmil	5.63	2.75	2.50	
BDR-25-050		1/0 Sol. - 500 kcmil	5.63	2.75	2.50	
BDR-25-100		4/0 Sol. - 1000 kcmil	6.13	2.75	3.00	
BDR-25-200		500 - 2000 kcmil	6.13	2.75	3.00	
BDR-30-025	3	6 Sol. - 250 kcmil	6.13	3.25	2.50	
BDR-30-050		1/0 Sol. - 500 kcmil	6.13	3.25	2.50	
BDR-30-200		500 - 2000 kcmil	6.63	3.25	3.00	