


Heavy Duty One Hole Cast Copper Lugs - Side Formed for Diesel Locomotive Cable (DLO)

Type LL-S-SF

- Heavy duty cast copper compression lugs for traction motor applications
- Cast out of pure copper alloy for high conductivity
- Side formed design allows for conductor offset from mounting surface
- Electro-tin plated for corrosion resistance
- Suitable for installation with existing hydraulic crimping tools



CATALOG NUMBER	DLO CONDUCTOR SIZE	G BOLT SIZE	APPROXIMATE DIMENSIONS (IN.)						T&B DIE INDEX NO.
			L	F	E	O	W	T	
LL-49765-S-SF	150/24	1/4	1.88	.81	.38	.66	.63	.19	50
LL-47244-S-SF	225/24	3/8	2.13	1.00	.44	.72	.81	.22	54
LL-41157-S-SF	275/24	3/8	2.13	1.00	.44	.72	.81	.22	54
LL-53178-S-SF	325/24	3/8	2.13	1.00	.44	.72	.81	.22	54
LL-45087-S-SF	375/24	3/8	2.50	1.25	.56	.78	1.00	.25	60
LL-44593-S-SF	450/24	5/8	2.50	1.25	.53	.78	1.00	.25	60
LL-41158-S-SF	450/24	3/8	2.50	1.25	.53	.78	1.00	.25	60
LL-49332-S-SF	550/24	5/8	2.88	1.25	.75	1.05	1.19	.31	76
LL-44146-S-SF	550/24	3/8	2.88	1.50	.75	1.05	1.19	.31	76
LL-41159-S-SF	550/24	1/2	2.88	1.50	.75	1.05	1.19	.31	76
LL-42608-S-SF	650/24	1/2	2.88	1.50	.75	1.05	1.19	.31	76
LL-41160-S-SF	775/24	1/2	2.88	1.50	.75	1.05	1.19	.31	76
LL-40305-S-SF	775/24	3/8	3.06	1.50	.75	1.05	1.19	.31	76
LL-40744-S-SF	775/24	5/8	3.31	1.94	.75	1.05	1.19	.31	76
LL-42873-S-SF	925/24	1/2	3.38	1.50	.75	1.16	1.19	.34	87
LL-41149-S-SF	925/24	5/8	3.38	1.50	.75	1.16	1.19	.34	87
LL-47526-S-SF	1100/24	1/2	4.00	2.00	.88	1.34	1.63	.41	99
LL-44127-S-SF	1325/24	1/2	4.00	2.00	.88	1.38	1.63	.41	107
LL-44231-S-SF	1600/24	1/2	4.25	2.13	1.00	1.44	1.63	.44	112
LL-47742-S-SF	1600/24	3/4	4.25	2.13	1.00	1.44	1.63	.44	112
LL-47833-S-SF	1600/24	3/8	4.25	2.13	1.00	1.44	1.63	.44	112
LL-40862-S-SF	1925/24	1/2	4.25	2.13	1.00	1.44	1.63	.44	112
LL-50747-S-SF	2300/24	5/8	4.75	2.38	1.19	1.66	1.88	.50	130

For blank pad, add suffix "-U" to catalog number

Above terminals can be installed with the following T&B Tooling: 12 ton head (13642), 20 ton head (21920), and 40 ton head (21940)

T&B is a registered trademark of its respective company