


Heavy Duty Two Hole Cast Copper Lugs - Side Formed for Diesel Locomotive Cable (DLO)

Type LL-D-SF

- Heavy duty cast copper compression lugs for traction motor applications
- Cast out of pure copper alloy for high conductivity
- Side formed design allows for conductor offset from mounting surface
- Electro-tin plated for corrosion resistance
- Suitable for installation with existing hydraulic crimping tools



CATALOG NUMBER	DLO CONDUCTOR SIZE	G BOLT SIZE	APPROXIMATE DIMENSIONS (IN.)							T & B DIE INDEX NO.
			L	F	D	E	O	W	T	
LL-51797-D-SF	150/24	1/4	3.06	2.00	1.00	.34	.66	.63	.19	50
LL-49763-D-SF	225/24	3/8	3.13	2.00	1.00	.50	.72	.81	.22	54
LL-49764-D-SF	275/24	3/8	3.13	2.00	1.00	.50	.72	.81	.22	54
LL-46111-D-SF	450/24	1/2	4.25	3.00	1.25	.63	.78	1.00	.25	60
LL-49238-D-SF	550/24	3/8	3.31	1.94	1.00	.50	1.05	1.19	.31	76
LL-41147-D-SF	550/24	1/2	4.38	3.00	1.75	.63	1.05	1.19	.31	76
LL-47272-D-SF	650/24	1/2	4.38	3.00	1.75	.63	1.05	1.19	.31	76
LL-50774-D-SF	775/24	5/16	2.88	1.50	.81	.31	1.05	1.19	.31	76
LL-52078-D-SF	775/24	5/16	3.31	1.94	.88	.75	1.05	1.19	.31	76
LL-40467-D-SF	775/24	3/8	3.31	1.94	1.00	.50	1.05	1.19	.31	76
LL-49761-D-SF	775/24	1/2	4.38	3.00	1.75	.63	1.05	1.19	.31	76
LL-40743-D-SF	925/24	3/8	4.38	2.50	1.00	.44	1.16	1.19	.34	87
LL-41152-D-SF	925/24	3/8	5.38	3.50	1.00	.44	1.16	1.19	.34	87
LL-47521-D-SF	925/24	1/2	5.38	3.50	1.75	.63	1.16	1.19	.34	87
LL-50963-D-SF	1100/24	1/2	5.50	3.50	1.75	.63	1.38	1.63	.41	107
LL-41151-D-SF	1325/24	3/8	5.50	3.50	1.00	.50	1.38	1.63	.41	107
LL-41148-D-SF	1325/24	1/2	5.50	3.50	1.75	.63	1.38	1.63	.41	107
LL-49758-D-SF	1600/24	1/2	5.63	3.50	1.75	.63	1.44	1.63	.44	112
LL-52943-D-SF	1925/24	3/8	4.00	2.06	1.00	.44	1.44	2.00	.31	112
LL-41150-D-SF	1925/24	3/8	4.25	2.13	1.00	.44	1.44	1.63	.44	112
LL-42683-D-SF	1925/24	1/2	5.63	3.50	1.75	.63	1.44	1.63	.44	112
LL-49532-D-SF	2000/24	1/2	5.63	3.50	1.75	.63	1.44	1.63	.44	112
LL-47522-D-SF	2300/24	1/2	5.88	3.50	1.75	.63	1.66	1.88	.50	130
LL-50651-D-SF	2750/24	1/2	6.63	3.50	1.75	.63	1.91	2.13	.56	150

For blank pad, add suffix "-U" to catalog number

Above terminals can be installed with the following T&B Tooling: 12 ton head (13642), 20 ton head (21920), and 40 ton head (21940)

T&B is a registered trademark of its respective company