


Standard Barrel - One Hole Tongue with Inspection Window

Type BLU-S

- Manufactured from high conductivity seamless copper tubing
- Tin-plated to inhibit corrosion
- Beveled entry for easy cable insertion
- Inspection window to ensure full cable insertion
- Color coded barrels are marked with die index numbers
- Connectors are suitable for voltages up to 35 KV
- 45° and 90° angles are UL listed and CSA certified
- Connectors are UL listed and CSA certified with Penn-Union, Burndy, T&B, Huskie, Greenlee and Versa-Crimp® style tooling



BLU-S

BLU-S DIMENSIONS & INSTALLATION TOOLING INFORMATION

CATALOG NUMBER	COPPER CONDUCTOR SIZE	STUD HOLE SIZE	FIGURE DIMENSIONS (IN.)					INSTALLATION TOOLING				WIRE STRIP LENGTH
			TONGUE WIDTH "W"	TONGUE LENGTH "C"	TONGUE THICKNESS "T"	BARREL LENGTH "B"	OVERALL LENGTH "L"	COLOR CODE	PENN-UNION DIELESS MECHANICAL TOOLS	BURNDY DIE INDEX NO. /TOOL	PENN-UNION DIE CATALOG NO.	
BLU-8S14	8 AWG	#10	.37	.50	.08	.41	1.09	Red	TDM-250 or TDM-500	6	T-49	1/2"
BLU-8S15		1/4"	.37	.56	.08	.41	1.14					
BLU-8S16Δ		5/16"	.60	.64	.07	.57	1.46					
BLU-8S17Δ		3/8"	.60	.64	.07	.58	1.52		-	Y644HS	-	11/16"
BLU-8S18Δ		1/2"	.70	1.00	.09	.57	1.72					
BLU-6S	6 AWG	#10	.41	.53	.09	.81	1.51	Blue	TDM-250 or TDM-500	7	T-7	15/16"
BLU-6S1		1/4"	.41	.69	.09	.81	1.67					
BLU-6S2		5/16"	.45	.75	.07	.82	1.78					
BLU-6S8		3/8"	.60	.88	.06	.81	1.97					
BLU-6S9+		1/2"	.70	.94	.08	.75	1.88		-	Y644HS	-	7/8"
BLU-5S	5 AWG	#10	.43	.56	.08	.81	1.61	Blue	TDM-250 or TDM-500	7	T-7	15/16"
BLU-5S1		1/4"	.43	.69	.08	.81	1.73					
BLU-5S2		5/16"	.61	.72	.06	.81	1.77					
BLU-5S3		3/8"	.61	.88	.06	.81	1.92					
BLU-4S	4 AWG	#10	.48	.56	.09	.81	1.61	Gray	TDM-250 or TDM-500	8	T-8	15/16"
BLU-4S1		1/4"	.48	.69	.09	.81	1.67					
BLU-4S10		5/16"	.48	.72	.09	.81	1.76					
BLU-4S2		3/8"	.60	.88	.08	.81	1.97					
BLU-4S4 +		1/2"	1.12	1.12	.13	.83	2.22					
BLU-3S	3 AWG	#10	.53	.56	.09	.88	1.67	White	TDM-250 or TDM-500	9	T-9	1"
BLU-3S1		1/4"	.53	.69	.09	.88	1.80					
BLU-3S2		5/16"	.53	.75	.09	.88	1.86					
BLU-3S3		3/8"	.59	.88	.08	.88	1.98					

BLU-S DIMENSIONS & INSTALLATION TOOLING INFORMATION (Continued)

CATALOG NUMBER	COPPER CONDUCTOR SIZE	STUD HOLE SIZE	FIGURE DIMENSIONS (IN.)					INSTALLATION TOOLING				WIRE STRIP LENGTH
			TONGUE WIDTH "W"	TONGUE LENGTH "C"	TONGUE THICKNESS "T"	BARREL LENGTH "B"	OVERALL LENGTH "L"	COLOR CODE	PENN-UNION DIELESS MECHANICAL TOOLS	BURNDY DIE INDEX NO. /TOOL	PENN-UNION DIE CATALOG NO.	
BLU-2S15	2 AWG	#10	.59	.69	.11	.88	1.73	Brown	TDM-250 or TDM-500	10	T-10	1"
BLU-2S		1/4"	.59	.69	.11	.88	1.73					
BLU-2S1		5/16"	.59	.75	.11	.88	1.86					
BLU-2S2		3/8"	.59	.87	.11	.88	1.98					
BLU-2S10		1/2"	.82	1.13	.10	.88	2.25					
BLU-1S9	1 AWG	1/4"	.67	.56	.11	.62	1.42	Green	TDM-250 or TDM-500	11	T-11	3/4"
BLU-1S		5/16"	.67	.75	.11	.88	1.86					1"
BLU-1S1		3/8"	.67	.87	.11	.94	2.05					1-1/16"
BLU-1S4A		1/2"	.70	1.06	.09	.82	2.03		-	Y644HS	-	15/16"
BLU-1/0S19	1/0 AWG	1/4"	.73	.87	.12	.87	2.05	Pink	TDM-250 or TDM-500	12	T-12	1"
BLU-1/0S		5/16"	.73	.87	.12	.88	2.05					
BLU-1/0S1		3/8"	.73	.87	.12	.88	2.05					
BLU-1/0S20		1/2"	.73	1.06	.12	.87	2.25					
BLU-2/0S20	2/0 AWG	1/4"	.81	.81	.12	.94	2.06	Black	TDM-250 or TDM-500	13	T-13	1-1/16"
BLU-2/0S21		5/16"	.81	.81	.12	.94	2.06					
BLU-2/0S		3/8"	.81	.87	.12	.94	2.11					
BLU-2/0S4		1/2"	.81	1.12	.12	.94	2.37					
BLU-3/0S14	3/0 AWG	1/4"	.89	.81	.12	.75	1.94	Orange	TDM-250 or TDM-500	14	T-14	1-1/8"
BLU-3/0S15		5/16"	.89	.81	.12	.75	1.94					
BLU-3/0S		3/8"	.89	.87	.12	1.00	2.25					
BLU-3/0S1		1/2"	.89	1.12	.12	1.00	2.50					
BLU-4/0S19	4/0 AWG	1/4"	1.00	.78	.14	1.00	2.22	Purple	TDM-250 or TDM-500	15	T-15	1-1/8"
BLU-4/0S25		5/16"	1.00	.78	.14	1.00	2.22					
BLU-4/0S		3/8"	1.00	.87	.14	1.00	2.31					
BLU-4/0S1		1/2"	1.00	1.09	.14	1.00	2.50					
BLU-02S54	250 kcmil	1/4"	1.09	.78	.15	1.06	2.34	Yellow	TDM-250 or TDM-500	16	T-16	1-3/16"
BLU-02S55		5/16"	1.09	.78	.15	1.06	2.34					
BLU-02S52		3/8"	1.09	1.13	.15	1.06	2.69					
BLU-02S5		1/2"	1.09	1.13	.15	1.06	2.69					
BLU-030S6	300 kcmil	5/16"	1.19	.78	.16	1.06	2.41	White	TDM-500	17	T-17	1-3/16"
BLU-030S7		3/8"	1.19	1.09	.16	1.06	2.75					
BLU-030S		1/2"	1.19	1.09	.16	1.06	2.75					
BLU-030S8		5/8"	1.19	1.69	.16	1.06	3.31					
BLU-03S51	350 kcmil	3/8"	1.28	.88	.17	1.13	2.63	Red	TDM-500	18	T-18	1-1/4"
BLU-03S5		1/2"	1.28	1.16	.17	1.13	2.91					
BLU-03S53		5/8"	1.28	1.41	.17	1.13	3.16					
BLU-040S4	400 kcmil	1/2"	1.39	1.19	.19	1.19	3.06	Blue	TDM-500	19	T-19	1-5/16"
BLU-040S		5/8"	1.39	1.44	.19	1.19	3.31					
BLU-04S51	450 kcmil	1/2"	1.45	1.19	.22	1.19	3.06	Blue	TDM-500	19	T-19	1-5/16"
BLU-04S5		5/8"	1.45	1.44	.22	1.18	3.31					
BLU-050S2	500 kcmil	1/2"	1.53	1.13	.21	1.38	3.28	Brown	TDM-500	20	T-20	1-1/2"
BLU-050S		5/8"	1.53	1.44	.21	1.38	3.63					
BLU-060S	600 kcmil	5/8"	1.72	1.75	.27	1.38	3.97	Green		22	T-22	1-1/2"
BLU-060S1		1/2"	1.72	1.75	.27	1.38	3.97					
BLU-06S54	650 kcmil	5/8"	1.78	1.75	.27	1.38	3.97	Pink		300	T-300	1-1/2"
BLU-06S55		1/2"	1.78	1.75	.27	1.38	3.97					
BLU-07S5	750 kcmil	5/8"	1.91	1.75	.27	1.63	4.31	Black		24	T-24	1-3/4"
BLU-080S	800 kcmil	5/8"	1.96	1.88	.25	1.63	4.53	Orange		25	T-25P	1-3/4"
BLU-100S	1000 kcmil	5/8"	2.17	1.75	.33	1.88	4.75	White		27	T-27P	2"
BLU-100S4		3/4"	2.17	1.88	.33	1.88	4.88					
BLU-150S	1500 kcmil	3/4"	2.69	2.19	.39	2.00	5.47	Green		31	T-31P	2-1/8"
BLU-200S	2000 kcmil	3/4"	3.07	2.31	.46	2.25	5.94	Brown		34	-	2-3/8"

Δ cULus listed

• Not UL listed

+ Not CSA certified

• For 45° or 90° BENT TONGUES add suffix "-45" for 45 deg. or "-90" for 90 deg. to the catalog number

• Connectors from 8 AWG - 2000 kcmil are UL listed per UL486A-B and CSA certified per C22.2 No.65 for POWER applications

• Connectors from 8 AWG - 500 kcmil are UL listed for grounding, bonding and direct burial applications per UL467

• Connectors from 8 AWG - 250 kcmil are CSA certified for grounding, bonding and direct burial applications per C22.2 No.41