



COPPER PENN-CRIMPS® • TYPE H



Made with high conductivity, electrolytic copper, annealed and electro-tin plated to resist corrosion. Hook design allows for easy installation because mounting screw need not be removed. Available non-insulated or with NEMA color coded nylon or vinyl insulation. Insulation is flared for wire insulation support. The combination of these features and the fact that our products exceed UL and CSA requirements guarantee a high quality connection.

NON-INSULATED HOOK TERMINAL

BUTTED SEAM

Catalog Number	Copper Cond. Range	Stud Size	Stock Size (in)	Approx. Dimen. in Inches					
				A	W	C	M	B	ID
H1A-6	22-18	6	.030	.69	.34	.25	.54	.250	.070
H1A-8	22-18	8	.030	.69	.34	.25	.54	.250	.070
H1A-10	22-18	10	.030	.69	.34	.25	.54	.250	.070
H1B-6	16-14	6	.030	.69	.34	.25	.54	.250	.090
H1B-8	16-14	8	.030	.69	.34	.25	.54	.250	.090
H1B-10	16-14	10	.030	.69	.34	.25	.54	.250	.090
H1C-6	12-10	6	.040	.72	.38	.28	.54	.250	.130
H1C-8	12-10	8	.040	.72	.38	.28	.54	.250	.130
H1C-10	12-10	10	.040	.72	.38	.28	.54	.250	.130

INSULATED HOOK TERMINAL

VINYL INSULATED - BUTTED SEAM

Catalog Number	Copper Cond. Range	Stud Size	Color Code (ins)	Stock Size (in)	Max. Insul. Diam.	Approx. Dimen. in Inches					
						A	W	C	M	B	ID
H4A-6	22-18	6	R	.030	.15	1.01	.34	.25	.85	.250	.070
H4A-8	22-18	8	R	.030	.15	1.01	.34	.25	.85	.250	.070
H4A-10	22-18	10	R	.030	.15	1.01	.34	.25	.85	.250	.070
H4B-6	16-14	6	B	.030	.18	.93	.34	.25	.78	.250	.090
H4B-8	16-14	8	B	.030	.18	.93	.34	.25	.78	.250	.090
H4B-10	16-14	10	B	.030	.18	.93	.34	.25	.78	.250	.090
H4C-6	12-10	6	Y	.040	.26	.99	.38	.28	.80	.250	.130
H4C-8	12-10	8	Y	.040	.26	.99	.38	.28	.80	.250	.130
H4C-10	12-10	10	Y	.040	.26	.99	.38	.28	.80	.250	.130

NYLON INSULATED - BUTTED SEAM WITH BRASS SLEEVE

H6A-6	22-18	6	R	.030	.15	.93	.34	.25	.78	.250	.070
H6A-8	22-18	8	R	.030	.15	.93	.34	.25	.78	.250	.070
H6A-10	22-18	10	R	.030	.15	.93	.34	.25	.78	.250	.070
H6B-6	16-14	6	B	.030	.18	.93	.34	.25	.78	.250	.090
H6B-8	16-14	8	B	.030	.18	.93	.34	.25	.78	.250	.090
H6B-10	16-14	10	B	.030	.18	.93	.34	.25	.78	.250	.090
H6C-6	12-10	6	Y	.040	.26	1.00	.38	.28	.81	.250	.130
H6C-8	12-10	8	Y	.040	.26	1.00	.38	.28	.81	.250	.130
H6C-10	12-10	10	Y	.040	.26	1.00	.38	.28	.81	.250	.130