



COPPER PENN-CRIMPS® • TYPES FDC AND FSC



FDC



FSC

Nylon insulated, high strength spring quality connector. Locking feature provided to hold male snap plug securely in place while providing all the benefits of a two way quick disconnect. As with all Penn-Crimps the highest quality is assured.



FEMALE CONNECTOR

DOUBLE



Catalog Number	Copper Cond. Range	Stud Size	Stock Size (in)	Approx. Dimen. in Inches
				A
FDC-156	16-14	.156	.020	1.38

SINGLE

FSCA-156F	22-18	.156	.020	1.025
FSC-156F	16-14	.156	.020	1.025



COPPER PENN-CRIMPS® • TYPES CFR AND CM



Same high quality construction as Types FR and M female and male disconnects. Both CFR and CM disconnects feature full length nylon insulation which extends beyond the metal terminal insert to provide a completely insulated two piece connection, which is protected against accidental shorting. Exceeds UL standards to produce a high quality connection.

FULLY INSULATED MALE AND FEMALE DISCONNECTS

FEMALE

Catalog Number	Copper Cond. Range	Tab Size (in)	Max. Insul. Diam.	Approximate Dimensions in Inches		
				A	W	ID
CFR4NA250F	22-18	.032 x .250	.15	.98	.39	.070
CFR4NB250F	16-14	.032 x .250	.18	.98	.39	.090

MALE

CM4TNA250F	22-18	.032 x .250	.15	1.02	.47	.050
CM4TNB250F	16-14	.032 x .250	.18	1.02	.47	.090