

PENN-CRIMPS® TERMINAL KITS • TYPES MK 40-MK 71, & PK 50NT-PK 58



MK 42



MK 70



MK 71



PK 55



PK 57



PK 58

The MK kits come with a variety of terminals and connectors for industrial, commercial, maintenance, construction and general use purposes. The kits are packaged in a rugged, heavy duty, hinged metal box.

Catalog Number	Description
MK-40	Metal Kit Box with Scoop Compartments
MK-41	Metal Kit Box with Scoop Compartments and HTS-1440 Crimping Tool
MK-42	Metal Kit Box with Scoop Compartments, HTS-1440 Crimping Tool and 500 Assorted Vinyl Insulated Terminals and Connectors
MK-43	Metal Kit Box with Scoop Compartments, HTS-1440 Tool and 1000 Assorted Non-Insulated Terminals and Connectors
MK-70	Metal Kit Box with Scoop Compartments, 100 7 1/2" Cable Ties and 1155 Assorted Vinyl Insulated Terminals and Connectors
MK-71	Metal Kit Box with Scoop Compartments, HTS 1440 Tool and 1155 Assorted Vinyl Insulated Terminals and Connectors

Catalog Number	Description
PK-50NT	Kit, No Tool 18 Popular Vinyl Items
PK-55	HVAC/R Maintenance and Repair Kit 18 popular items
PK-57	Hi-Temp Terminal Kit 12 popular Items (900°F)
PK-58	10 popular Items (900°F) 2 popular Porcelain Wire Nuts 1 roll High Temp Glass cloth tape

PENN-NUTS • PN SERIES CONNECTORS, KNURLED AND WING STYLE



KNURLED STYLE:

Cat. No.	Color	Application	OAL
PNGK	Grey	*#22 to #16 AWG Min: 1 #20 w/1 #22 Max: 2 #16	.58
PNBK	Blue	*#22 to #16 AWG Min: 3 #22 Max: 3 #16	.70
PNOK	Orange	**#22 to #14 AWG Min: 3 #20 Max: 4 #16 & 1 #20	.84
PNYK	Yellow	***#18 to #10 AWG Min: 1 #14 & 1 #18 Max: 4 #14	.94
PNRK	Red	***#18 to #10 AWG Min: 2 #14 Max: 2 #10 & 2 #12	1.06

*Connections rated at 300 V Max.

**Connections rated at 300 V Max. and 600 V Max. Connections rated at 600+ V Max. for Building Wiring are rated at 1000V Max. in Fixtures and Signs.

The range of wire combinations fills the requirements of many of the more typical connections made.

Knurled style offers the industry's standard screw-on connector. Winged style offers a high-leverage easy on live spring design.

Available in packages of either kegs (containing polybags), boxes, or clamshells.

Standard packaging in boxes of 1,000, 100, and as bulk packed kegs of poly bags of 500 (250 for PNRK). 1,000 and 100 quantity boxes are available by using a suffix of "-M" (for 1,000) or "-C" (for 100).

All of the Penn-Nuts are UL listed and have a temperature rating of 105°C (221°F).

WINGED STYLE:

Cat. No.	Color	Application	OAL
PNYW	Yellow	***#22 to #10 AWG Min: 2 #18 Max: 3 #12	1.03
PNRW	Red	***#18 to #10 AWG Min: 2 #14 Max: 5 #12	1.25