

A. Featured Products

SmartZone™ G5 Power Distribution Units (PDUs)

B. Copper Systems



1U (SLIM)



1U



2U



0U HALF

C. Fiber Systems



0U HALF 2-sided



0U MID



0U FULL



0U FULL 2-sided

D. Industrial Networks

Dimensions

| Form Factor | Height In. (mm) | Width In. (mm) | Depth In. (mm) |
|-------------------|-----------------|----------------|----------------|
| 1U (SLIM) | 1.6 (40.6) | 17.5 (444.5) | 2.0 (50.8) |
| 1U | 1.7 (43.2) | | 7.8 (198.1) |
| 2U | 3.4 (86.4) | | |
| 0U HALF | 32.2 (817.9) | 2.0 (50.8) | 2.1 (53.3) |
| 0U HALF (2 sided) | 36 (914.4) | | 4.4 (111.8) |
| 0U MID | 58.7 (1491) | | 2.1 (53.3) |
| 0U FULL | 68.9 (1750.1) | | 4.4 (111.8) |
| 0U FULL (2 sided) | 71.7 (1821.2) | | |

Mounting: Vertical units provide up to 48 outlets and do not occupy the EIA space. Horizontal units provide up to 16 outlets and mount in standard (1U or 2U) EIA rack space.

K. Surface Raceway

L. Cabinets & Rack Systems

M. Power Management

N. Grounding & Bonding

O. Identification Products

P. Cable Management Accessories

Q. Part Number Index

Continued on next page

A.
Featured
Products

Monitored Switched (MS Series)

- Provides aggregate power monitoring as well as outlet level switching capabilities for individual outlets or an outlet bank
- Can also be used for environmental monitoring through sensors and electronic rack access control through electronic swing-handles (each sold separately)

B.
Copper
Systems

C.
Fiber
Systems

D.
Industrial
Networks

E.
Audio
Video
Systems

F.
Keystone
Cabling
Systems

G.
Faceplates,
Frames &
Surface
Mount Boxes

H.
Zone
Cabling

J.
Cable
Routing
Systems

K.
Surface
Raceway

L.
Cabinets
& Rack
Systems

M.
Power
Management

N.
Grounding
& Bonding

O.
Identification
Products

P.
Cable
Management
Accessories

Q.
Part
Number
Index

| Part Number | Input Current per Phase | Form Factor | Input Plug Type | Apparent Power kVA | Outlet Count | Outlet Type | Length In. | Width In. | Depth In. at Outlet Position |
|----------------------------|-------------------------|-------------|-----------------|--------------------|--------------|-------------|-----------------|-----------|------------------------------|
| 100-240VAC, 1-Phase | | | | | | | | | |
| P08E14M | 15 | 1U | 5-15P | 1.4 | 8 | (8)5-20R | 1.7 | 17.5 | 10.6 |
| P08E16M | 20 | | L5-20P | 1.9 | | | | | |
| P08E18M | | | OU HALF | L6-20P | | 3.3 | | | |
| P16E24M | 30 | OU FULL | | L6-30P | 5.0 | 24 | (12)C13, (4)C19 | 36.1 | 2.0 |
| P24E28M | | | 68.9 | | | | | | |

208VAC, 3-Phase

| | | | | | | | | | |
|---------|----|---------|---------|-------------------|---------|------------------|------|-----|-----|
| P24E29M | 30 | OU FULL | L15-30P | 8.6 | 24 | (18)C13, (6)C19 | 68.9 | 2.0 | 2.1 |
| P36E34M | | | | | 36 | (30)C13, (6)C19 | | | |
| P24E30M | | | 24 | | L21-30P | (18)C13, (6)C19 | | | |
| P36E35M | | | | | | 36 | | | |
| P24E31M | 50 | | CS8365C | 14.4 | 24 | (12)C13, (12)C19 | | | |
| P36E12M | | | | | 36 | (30)C13, (6)C19 | | | |
| P24E32M | | | | | | 60 | | | |
| | | | | IEC 60309 3P+E 9h | | | | | |

See pages M.7–M.9 for a complete line of Panduit SmartZone™ G5 iPDU compatible accessories and power cords.

Monitored Per Outlet (MPO Series)

- Can provide outlet level and aggregate power monitoring to quickly identify potential power issues and reclaim available or under-utilized power capacity at the outlet level
- Can also be used for environmental monitoring through sensors and electronic rack access control through electronic swing-handles (each sold separately)

| Part Number | Input Current per Phase | Form Factor | Input Plug Type | Apparent Power kVA | Outlet Count | Outlet Type | Length In. | Width In. | Depth In. at Outlet Position |
|----------------------------|-------------------------|-------------|-----------------|--------------------|--------------|-----------------|------------|-----------|------------------------------|
| 100-240VAC, 1-Phase | | | | | | | | | |
| P24F01M | 30 | OU FULL | NEMA L6-30P | 5.0 | 24 | (20)C13, (4)C19 | 68.9 | 2.0 | 2.1 |
| 208VAC, 3-Phase | | | | | | | | | |
| P24F03M | 30 | OU FULL | NEMA L21-30P | 8.6 | 24 | (18)C13, (6)C19 | 68.9 | 2.0 | 2.1 |

See pages M.7–M.9 for a complete line of Panduit SmartZone™ G5 iPDU compatible accessories and power cords.

Continued on next page