

A.
Featured
Products

B.
Copper
Systems

C.
Fiber
Systems

D.
Industrial
Networks

E.
Audio
Video
Systems

F.
Keystone
Cabling
Systems

G.
Faceplates,
Frames &
Surface
Mount Boxes

H.
Zone
Cabling

J.
Cable
Routing
Systems

K.
Surface
Raceway

L.
Cabinets
& Rack
Systems

M.
Power
Management

N.
Grounding
& Bonding

O.
Identification
Products

P.
Cable
Management
Accessories

Q.
Part
Number
Index

Monitored Switched (MS Series)

- Provides aggregate power monitoring as well as outlet level switching capabilities for individual outlets or an outlet bank
- Can also be used for environmental monitoring through sensors and electronic rack access control through electronic swing-handles (each sold separately)

Part Number	Input Current per Phase	Form Factor	Input Plug Type	Apparent Power kVA	Outlet Count	Outlet Type	Length In.	Width In.	Depth In. at Outlet Position
100-240VAC, 1-Phase									
P08E14M	15	1U	5-15P	1.4	8	(8)5-20R	1.7	17.5	10.6
P08E16M	20		L5-20P	1.9					
P08E18M			L6-20P	3.3					
P16E24M	30	OU HALF		L6-20P	3.3	16	(12)C13, (4)C19	36.1	2.0
P24E28M	30	OU FULL	L6-30P	5.0	24	(12)C13, (4)C19	68.9		

208VAC, 3-Phase

P24E29M	30	OU FULL	L15-30P	8.6	24	(18)C13, (6)C19	68.9	2.0	2.1
P36E34M					36	(30)C13, (6)C19			
P24E30M					24	(18)C13, (6)C19			
P36E35M					36	(30)C13, (6)C19			
P24E31M	50		CS8365C	14.4	24	(12)C13, (12)C19			
P36E12M					36	(30)C13, (6)C19			
P24E32M					60	IEC 60309 3P+E 9h			

See pages M.7–M.9 for a complete line of Panduit SmartZone™ G5 iPDU compatible accessories and power cords.

Monitored Per Outlet (MPO Series)

- Can provide outlet level and aggregate power monitoring to quickly identify potential power issues and reclaim available or under-utilized power capacity at the outlet level
- Can also be used for environmental monitoring through sensors and electronic rack access control through electronic swing-handles (each sold separately)

Part Number	Input Current per Phase	Form Factor	Input Plug Type	Apparent Power kVA	Outlet Count	Outlet Type	Length In.	Width In.	Depth In. at Outlet Position
100-240VAC, 1-Phase									
P24F01M	30	OU FULL	NEMA L6-30P	5.0	24	(20)C13, (4)C19	68.9	2.0	2.1
208VAC, 3-Phase									
P24F03M	30	OU FULL	NEMA L21-30P	8.6	24	(18)C13, (6)C19	68.9	2.0	2.1

See pages M.7–M.9 for a complete line of Panduit SmartZone™ G5 iPDU compatible accessories and power cords.

Continued on next page