


## Aluminum Dual Rated Lugs - One Hole Tongue Type LA

For use with one copper or aluminum conductor

- Manufactured from high strength aluminum alloy extrusion
- Electro-tin plated to ensure minimum contact resistance and protection against corrosion when used with copper wire
- Connectors are rated for 600 V, 90°C applications
- The use of oxide inhibitor is recommended for all aluminum terminations



| CATALOG NUMBER | CONDUCTOR RANGE    | FIGURE DIMENSIONS (IN.) |      |      |     |      |     |          | MTG. BOLT SIZE | HEX SIZE |
|----------------|--------------------|-------------------------|------|------|-----|------|-----|----------|----------------|----------|
|                |                    | L                       | W    | H    | T   | B    | C   | D (DIA.) |                |          |
| LA-6           | 14 Str. - 4 Str.   | 1.06                    | .50  | .50  | .09 | .68  | .25 | .27      | 1/4            | Slot     |
| LA-6G          | 14 Str. - 4 Str.   | 1.06                    | .50  | .50  | .09 | .68  | .25 | .27      | 1/4            | Slot     |
| LA-2           | 14 Str. - 2 Str.   | 1.16                    | .50  | .55  | .11 | .69  | .31 | .27      | 1/4            | Slot     |
| LA2-516*       | 14 Str. - 2 Str.   | 1.16                    | .50  | .55  | .11 | .69  | .31 | .33      | 5/16           | Slot     |
| LA-0           | 14 Str. - 1/0 Str. | 1.46                    | .63  | .79  | .19 | .84  | .44 | .27      | 1/4            | Slot     |
| LA-2/0         | 14 Str. - 2/0 Str. | 1.46                    | .63  | .79  | .19 | .84  | .44 | .27      | 1/4            | 3/16     |
| LA-250         | 6 Str. - 250 kcmil | 2.00                    | 1.00 | 1.12 | .25 | 1.00 | .47 | .33      | 5/16           | 5/16     |
| LA-350         | 6 Str. - 350 kcmil | 2.25                    | 1.13 | 1.25 | .25 | 1.13 | .50 | .41      | 3/8            | 5/16     |
| LA-500         | 4 Str. - 500 kcmil | 2.81                    | 1.50 | 1.57 | .31 | 1.59 | .87 | .41      | 3/8            | 3/8      |
| LA-600         | 2 Str. - 600 kcmil | 3.19                    | 1.50 | 1.56 | .44 | 1.81 | .87 | .41      | 3/8            | 1/2      |
| LA-800         | 300 - 800 kcmil    | 3.37                    | 1.75 | 1.94 | .50 | 1.75 | .87 | .66      | 5/8            | 1/2      |
| LA-1000+       | 500 - 1000 kcmil   | 3.38                    | 1.75 | 1.94 | .50 | 1.75 | .68 | .66      | 5/8            | 1/2      |

\* UL listed only

+ UL listed and CSA certified

\*\* LA-6G provided with green plated set screw

- UL467 listed for grounding and bonding