


## Aluminum Dual Rated Lugs - Two Hole Tongue with Tandem Set Screws Type LLA2

For use with one copper or aluminum conductor

- Manufactured from high strength aluminum alloy extrusion
- Electro-tin plated to ensure minimum contact resistance and protection against corrosion when used with copper wire
- Two hole mounting pad allows for maximum surface contact in heavy duty applications
- Tandem set screws provide superior mechanical performance
- Connectors are rated for 600 V, 90°C applications
- The use of oxide inhibitor is recommended for all aluminum terminations



486A-486B  
LISTED  
AL9CU



| CATALOG NUMBER | CONDUCTOR RANGE    | FIGURE DIMENSIONS (IN.) |      |      |     |      |     |          |      | MTG. BOLT SIZE | HEX SIZE |
|----------------|--------------------|-------------------------|------|------|-----|------|-----|----------|------|----------------|----------|
|                |                    | L                       | W    | H    | T   | B    | C   | D (DIA.) | E    |                |          |
| LLA2-500-S1    | 2 Str. - 600 kcmil | 5.58                    | 1.50 | 1.62 | .44 | 3.06 | .59 | .51      | 1.75 | 1/2            | 1/2      |
| LLA2-750-S1    | 300 - 800 kcmil    | 5.75                    | 1.75 | 1.94 | .50 | 3.00 | .87 | .51      | 1.38 |                | 1/2      |