

Bronze Ground Clamp Connectors

Type GT

- Clamp is manufactured from high copper content alloy
- Used to connect a range of parallel conductors perpendicular to rod, water pipe, or structured tube
- Furnished with silicon bronze bolt, nuts, and lockwashers for corrosion resistance
- Use one groove for run and other for tap to equipment
- Suitable for direct burial in earth or concrete
- Single wrench installation
- UL 467 listed



CATALOG NUMBER	ACCOMMODATES		CONDUCTOR RANGE	FIGURE DIMENSIONS (IN.)				BOLT SIZE
	ROD	IPS		A	B	C	D	
GT-1	1/2	1/4	8 Sol. - 4 Str.	1.63	2.10	1.38	1.00	3/8
GT-2			4 Sol. - 2/0 Str.	2.00	2.79	1.25	1.00	3/8
GT-3			2/0 Sol. - 250 kcmil	2.50	2.60	1.38	1.00	3/8
GT-4	5/8 or 3/4	3/8	8 Sol. - 4 Str.	1.63	2.32	1.38	1.19	3/8
GT-5			4 Sol. - 2/0 Str.	2.00	2.44	1.38	1.13	3/8
GT-6			2/0 Sol. - 250 kcmil	2.50	2.80	1.50	1.13	3/8
GT-7 •			300 - 500 kcmil	2.75	2.75	1.63	1.31	3/8
GT-8	7/8 or 1	1/2 or 3/4	8 Sol. - 4 Str.	1.63	2.72	1.88	1.50	3/8
GT-9			4 Sol. - 2/0 Str.	2.00	3.31	1.44	1.50	3/8
GT-10			2/0 Sol. - 250 kcmil	2.50	3.31	1.69	1.50	3/8
GT-11 •			300 - 500 kcmil	2.75	3.72	2.00	1.50	3/8
GT-12 •			500 - 750 kcmil	3.13	3.75	3.25	1.63	1/2
GT-13	-	1	8 Sol. - 4 Str.	1.63	2.68	1.44	1.75	3/8
GT-14			4 Sol. - 2/0 Str.	2.00	3.25	1.88	1.75	3/8
GT-15			2/0 Sol. - 250 kcmil	2.50	3.47	1.88	1.75	3/8
GT-16 •			300 - 500 kcmil	2.75	3.75	2.00	1.75	3/8
GT-17 •			500 - 750 kcmil	3.13	4.13	2.25	1.88	1/2
GT-18	-	1 1/4	8 Sol. - 4 Str.	1.63	3.09	2.06	2.06	3/8
GT-19			4 Sol. - 2/0 Str.	2.00	3.70	2.06	2.06	3/8
GT-20			2/0 Sol. - 250 kcmil	2.50	3.70	2.06	2.06	3/8
GT-21 •			300 - 500 kcmil	2.75	4.13	2.25	2.19	1/2
GT-22 •			500 - 750 kcmil	3.75	4.38	2.50	2.31	5/8
GT-23 •			750 - 1000 kcmil	4.00	4.63	2.75	2.31	5/8
GT-24	-	1 1/2	8 Sol. - 4 Str.	1.56	3.88	2.25	2.31	3/8
GT-25			4 Sol. - 2/0 Str.	2.00	3.88	2.31	2.38	3/8
GT-26			2/0 Sol. - 250 kcmil	2.50	3.88	2.31	2.38	3/8
GT-27 •			300 - 500 kcmil	2.75	4.38	2.63	2.50	1/2
GT-28 •			500 - 750 kcmil	3.75	4.75	2.75	2.63	5/8
GT-29 •			750 - 1000 kcmil	4.00	5.00	2.88	2.63	5/8

• UL listing is limited to maximum wire size of 250 kcmil

