

Bronze Ground Clamp Connectors

Type GU

- Clamp is manufactured from high copper content alloy
- Used to connect two parallel cables or a looped cable to water pipe or tube
- Furnished with silicon bronze bolt, nuts, and lockwashers for corrosion resistance
- Suitable for direct burial in earth or concrete
- Single wrench installation
- UL 467 listed



CATALOG NUMBER	IPS SIZE	CONDUCTOR RANGE	FIGURE DIMENSIONS (IN.)				BOLT SIZE
			A	B	C	D	
GU-0	3/4	8 Sol. - 4 Str.	2.50	.88	2.63	1.50	3/8
GU-00		4 Sol. - 2/0 Str.	2.50	.88	2.63	1.50	3/8
GU-1	1	8 Sol. - 4 Str.	2.75	1.13	3.00	1.75	3/8
GU-2		4 Sol. - 2/0 Str.	2.75	1.13	3.25	1.75	3/8
GU-3		2/0 Sol. - 250 kcmil	2.75	1.25	3.50	1.75	3/8
GU-4	1 1/4	8 Sol. - 4 Str.	3.00	1.13	3.25	2.06	3/8
GU-5		4 Sol. - 2/0 Str.	3.00	1.25	3.50	2.06	3/8
GU-6		2/0 Sol. - 250 kcmil	3.00	1.38	3.75	2.06	3/8
GU-7	1 1/2	8 Sol. - 4 Str.	3.38	1.25	3.50	2.38	3/8
GU-8		4 Sol. - 2/0 Str.	3.38	1.38	3.63	2.38	3/8
GU-9		2/0 Sol. - 250 kcmil	3.38	1.50	3.75	2.38	3/8
GU-10	2	8 Sol. - 4 Str.	3.75	1.38	3.88	2.81	3/8
GU-11		4 Sol. - 2/0 Str.	3.75	1.38	4.13	2.81	3/8
GU-12		2/0 Sol. - 250 kcmil	3.75	1.38	4.25	2.81	3/8
GU-13		300 - 500 kcmil	4.00	1.50	4.63	2.94	1/2
GU-14	2 1/2	8 Sol. - 4 Str.	4.25	1.38	5.00	3.31	3/8
GU-15		4 Sol. - 2/0 Str.	4.25	1.38	5.13	3.31	3/8
GU-16		2/0 Sol. - 250 kcmil	4.25	1.38	5.25	3.31	3/8
GU-17		300 - 500 kcmil	4.50	1.50	5.50	3.44	1/2
GU-18		500 - 750 kcmil	4.50	1.56	5.44	3.44	1/2
GU-19	3	8 Sol. - 4 Str.	5.00	1.38	5.25	3.94	3/8
GU-20		4 Sol. - 2/0 Str.	5.00	1.38	5.50	3.94	3/8
GU-21		2/0 Sol. - 250 kcmil	5.00	1.38	5.75	3.94	3/8
GU-22		300 - 500 kcmil	5.25	1.50	6.00	4.06	1/2
GU-23		500 - 750 kcmil	5.50	1.75	6.38	4.19	5/8
GU-25	3 1/2	8 Sol. - 4 Str.	5.50	1.50	6.00	4.44	3/8
GU-26		4 Sol. - 2/0 Str.	5.50	1.50	6.13	4.44	3/8
GU-27		2/0 Sol. - 250 kcmil	5.50	1.50	6.25	4.44	3/8
GU-28		300 - 500 kcmil	5.75	1.75	6.38	4.56	1/2
GU-29		500 - 750 kcmil	6.00	1.88	6.63	4.69	5/8
GU-30		750 - 1000 kcmil	6.00	2.13	7.00	4.69	5/8
GU-31	4	8 Sol. - 4 Str.	6.00	1.50	6.50	4.94	3/8
GU-32		4 Sol. - 2/0 Str.	6.00	1.50	6.75	4.94	3/8
GU-33		2/0 Sol. - 250 kcmil	6.00	1.63	7.00	4.94	3/8
GU-34		300 - 500 kcmil	6.25	1.63	7.25	5.06	1/2
GU-35		500 - 750 kcmil	6.50	1.88	7.50	5.19	5/8
GU-36		750 - 1000 kcmil	6.50	2.13	7.75	5.19	5/8
GU-37		1200 - 1500 kcmil	6.50	2.38	8.13	5.19	5/8

• UL listing is limited to a maximum wire size of 250 kcmil

