


Bronze Ground Clamp Connectors - Rebar

Type KR-DB

- Manufactured from high strength cast copper alloy
- For use in harsh environments such as swimming pools, spas, agriculture, food processing, marine, communication grids, and others
- Lay in features allow continuous loop wiring
- Installs quickly, grips rebar between ridges and special teeth
- All hardware is stainless steel
- Suitable for direct burial in earth or concrete
- cULus 467 listed



CATALOG NUMBER	REBAR SIZE	CONDUCTOR RANGE		FIGURE DIMENSIONS (IN.)		
		MIN.	MAX.	L	W	H
KR-3-DB	3/8"	8 Sol.	6 Sol.	1.14	.74	1.50
KR-4-DB	1/2"	8 Sol.	4 Str.	1.35	.83	1.50



Bronze Universal Parallel Groove Clamp Connectors

Type UCR

- Manufactured from high strength bronze alloy
- Designed to clamp two copper conductors to flat surface or bus bar
- Furnished with silicon bronze hardware
- Accommodates a wide conductor range in both grooves
- Interlocking design ensures proper conductor alignment



CATALOG NUMBER	CONDUCTOR RANGE (EITHER GROOVE)	FIGURE DIMENSIONS (IN.)			BOLT SIZE
		L	W	H	
UCR-013	8 Sol. - 2/0 Str.	1.25	1.75	1.06	3/8
UCR-030	1/0 Sol. - 300 kcmil	1.75	2.31	1.38	1/2
UCR-050	250 - 500 kcmil	2.00	2.75	1.63	1/2
*UCR-075	300 - 750 kcmil	3.50	3.13	2.13	1/2

* Two bolts

