





Standard Flared Barrel - One Hole Tongue with Inspection Window

Type BLU-S-FL

- Suitable for use with Class B, C, I, K, H, G, M and DLO conductors ♦
- Manufactured from high conductivity seamless copper tubing
- Tin plated to inhibit corrosion
- Inspection window ensures full cable insertion
- Flared barrel entry provides easy cable insertion for fine stranded flexible cables and minimizes strain during flexing and movement
- Color coded barrels are marked with die index numbers
- Connectors are suitable for voltages up to 35 KV
- 45° and 90° angles are UL listed and CSA certified
- Connectors are UL listed and CSA certified with Penn-Union, Burndy, T&B, Huskie, Greenlee and Versa-Crimp® style tooling



CATALOG NUMBER	COPPER CONDUCTOR SIZE	STUD HOLE SIZE	FIGURE DIMENSIONS (IN.)					INSTALLATION TOOLING				WIRE STRIP LENGTH
			TONGUE WIDTH "W"	TONGUE LENGTH "C"	TONGUE THICKNESS "T"	BARREL LENGTH "B"	OVERALL LENGTH "L"	COLOR CODE	PENN-UNION DIELESS MECHANICAL TOOLS	BURNDY DIE INDEX NO.	PENN-UNION DIE CATALOG NO.	
BLU-3S2-FL	3 AWG	5/16	.53	.75	.09	.88	1.86	White	TDM-250XF	9	T-9	1"
BLU-1S-FL	1 AWG	5/16	.67	.75	.11	.88	1.86	Green		11	T-11	1"
BLU-1/0S-FL	1/0 AWG	5/16	.73	.87	.12	.88	2.05	Pink		12	T-12	1"
BLU-2/0S21-FL	2/0 AWG	5/16	.81	.81	.12	.94	2.06	Black		13	T-13	1-1/16"
BLU-2/0S-FL		3/8	.81	.87	.12	.94	2.11			14	T-14	1-1/8"
BLU-3/0S1-FL	3/0 AWG	1/2	.89	1.12	.12	1.00	2.50	Orange		15	T-15	1-1/8"
BLU-4/0S1-FL	4/0 AWG	1/2	1.00	1.09	.14	1.00	2.50	Purple		17	T-17	1-3/16"
BLU-030S-FL	300 kcmil	1/2	1.19	1.09	.16	1.06	2.75	White		18	T-18	1-1/4"
BLU-035S-FL	350 kcmil	1/2	1.28	1.16	.17	1.13	2.91	Red		19	T-19	1-5/16"
BLU-040S-FL	400 kcmil	5/8	1.39	1.44	.19	1.19	3.31	Blue		20	T-20	1-1/2"
BLU-050S-FL	500 kcmil	5/8	1.53	1.44	.21	1.38	3.63	Brown		22	T-22	1-1/2"
BLU-060S-FL	600 kcmil	5/8	1.72	1.75	.27	1.38	3.97	Green		24	T-24	1-3/4"
BLU-065S4-FL	650 kcmil	5/8	1.78	1.75	.27	1.38	3.97	Pink		27	T-27P	2"
BLU-075S-FL	750 kcmil	5/8	1.91	1.75	.27	1.63	4.31	Black		31	T-31P	2-1/8"
BLU-100S-FL	1000 kcmil	5/8	2.17	1.75	.33	1.88	4.75	White				
BLU-150S-FL	1500 kcmil	3/4	2.69	2.19	.39	2.00	5.47	Green				

♦ For additional wire size recommendations please refer to page 81

• For 45° or 90° BENT TONGUES add suffix "-45" for 45 deg. or "-90" for 90 deg. to the catalog number

- Connectors from 8 AWG - 2000 kcmil are UL listed per UL486A-B and CSA certified per C22.2 No.65 for POWER applications
- Connectors from 8 AWG - 500 kcmil are UL listed for grounding, bonding and direct burial applications per UL467
- Connectors from 8 AWG - 250 kcmil are CSA certified for grounding, bonding and direct burial applications per C22.2 No.41