

Cual-Aid #11C

- Use with compression lugs and splices
- Recommended for aluminum to aluminum, aluminum to copper, conduit threads, and bolted applications
- Non-melting, non-petroleum base compound with suspended zinc particles
- Has little or no effect on rubber or other insulating materials



CATALOG NUMBER	UNIT PACKAGING	CARTON QTY.
4OZN011C	4 oz. Squeeze Tube	12
1/2PTN011C	8 oz. Squeeze Bottle	12
PTN011C	1 pint Can	1
QTN011C	1 quart Can	1
GALN011C	1 gal. Can	1
5GALN011C	5 gal. Can	1
55GALN011C	55 gal. Drum	1

Cual-Aid #12C

- Recommended for aluminum to aluminum and aluminum to copper compression applications
- Non-melting, non-petroleum base compound with suspended zinc particles and abrasive grit
- Abrasive grit breaks down surface oxides improving conductivity
- Not for use on threads or bolted applications
- Has little or no effect on rubber or other insulating materials

CATALOG NUMBER	UNIT PACKAGING	CARTON QTY.
1/2PTN012C	8 oz. Squeeze Bottle	24
PTN012C	1 pint Can	1
QTN012C	1 quart Can	1
GALN012C	1 gal. Can	1
5GALN012C	5 gal. Can	1
55GALN012C	55 gal. Drum	1