

Protective Boots for Type K and SK Operators

Table 19.294: Protective Boots




For Non-Illuminated Push Buttons [152]		Clear Color for	Type [153]
Color	Type [153]		
Black	KU1	Standard knob selector switch	KU17
Red	KU2		
Blue	KU3		
Brown	KU4	Gloved-hand cap for use on standard knob selector switch	KU18
Green	KU5		
Yellow	KU6	Standard pilot light and maintained contact push buttons	KU27
Clear	KU7		
Clear	KU8		
(Provides Full Guard)		Illuminated push button with guard	KU47

NOTE: These Type KU protective boots are recommended for very dirty environments or severe hose down, but they are not required for UL Type 4 rating on the Type K operators or UL Type 4 or 4X rating on the Type SK operators. The K1 wrench (see [Wrenches for Type K and SK Operators, page 19-101](#)) is required for installation of these boots.

Closing Plates for Type K and SK Operators

Table 19.295: Closing Plates

 Round (1-1/2 in. Dia.)	Description	Type
	Gray	K51 [154]
Black	K52 [154]	

For Dimensions, see catalog 9001CT0001

[152] Use KU27 for maintained contact push buttons.
 [153] When ordering, add prefix 9001 to the catalog number.
 [154] Meets UL and NEMA 1, 2, 3, 4, 4X, 6, 12 and 13.