

No Photo
Available

Product Description

A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces, moisture, and cleans all in one.

Product Specifications

| | |
|------------------------------|---|
| Applications | Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc. |
| Unit Package Description | 1 Ounce (sample) |
| Brand | CRC |
| Generic Description 1 | Multi Purpose Precision Lubricant & Corrosion Inhibitor |
| Net Fill | 1 Wt Oz |
| UPC Code | 0 78254 03093 7 |
| Unit Dimensions-Inches | 4.13H x 1.38W x 1.38D |
| Units Per Case | 24 |
| Case Dimensions-Inches | Not Determined |
| Cases Per Pallet | 340 |
| Lbs. Per Case | 3 |
| I 2 of 5 Code | 30078254030938 |
| Appearance | Clear Blue-Green Liquid |
| Odor | Pleasant |
| Base Type | Petroleum |
| Flashpoint - TCC Method | 170°F |
| Specific Gravity | 0.8187 |
| Flammability | Flammable |
| Plastic Safe | No |
| Film Type | Non-Drying |
| Film Thickness | 0.025 to 0.075 Mils |
| Evaporation Rate | Not Determined |
| Dielectric Strength | 47,100 Volts |
| Working Temp [Degrees F] | -50 to 250°F |
| Propellant | Carbon Dioxide |
| NSF Category Code | H2 |
| NSF Registered | Yes |
| NSF Number | 017411 |
| Federal Specification Number | V-V-P-216,O-W-1284 |
| Aerosol Flammability Level | III |
| 360 Valve | Yes |
| DOT Proper Shipping Name | Consumer Commodity, ORM-D |
| VOC % (Federal) | 39.1 |
| VOC g/L (Federal) | 320.1 |
| VOC Lbs./Gal. (Federal) | 2.67 |
| VOC Compliant For CA | Yes |
| VOC Compliant For OTC/LADCO | Yes |
| VOC Category/Limit | Multi Purpose Lubricant (50%) |
| Removal (How To) | Remove with petroleum products, mineral spirits or any CRC degreaser or contact cleaner. |