



## Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------



## Main

Nominal Input Voltage	230 V
Other Input Voltages	220 V 240 V
Output voltage	230 V
Kw Rating	600 W
Rated power in VA	1000 VA
Plug standard	IEC 320 C14
Nb of power socket outlets	4 IEC 320 C13 2 IEC Jumpers
Number of rack unit	2U
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide Rack Mounting brackets USB cable

## General

Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Entry level
Redundant	No

## Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.01 in (43.2 cm)
Depth	15.98 in (40.6 cm)
Net Weight	45.24 lb(US) (20.52 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

## Input

Efficiency at full load	170...300 V adjustable 180...287 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	600 W
Transfer Time	2ms typical
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	57...63 Hz for 60 Hz nominal sync to mains

## Conformance

Product Certifications	CE CSA GOST VDE EAC
Standards	UL 1778

## Environmental

Acoustic level	42 dBA
Heat dissipation	46 Btu/h
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	4...6 year(s)
Battery power in VAh	170 VAh runtime
Battery Charge Power (Watts)	56 W rated

## Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	Multi-function LCD status and control console
Free slots	0

## Surge Protection and Filtering

Surge energy rating	459 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available