

Product data sheet

Specifications



APC Smart-UPS Ultra, 2200VA 120V 1U, with Lithium-Ion Battery, with Network Management Card Embedded

SRTL2K2RM1UNC

Main

Main Input Voltage	120 V 125 V
Other Input Voltage	120 V 125 V
Main Output Voltage	120 V
Other Output Voltage	120 V 125 V
Rated power in W	2200 W
Rated power in VA	2200 VA
Input Connection Type	NEMA 5-20P
Output connection type	3 NEMA 5-20R 1 NEMA L5-20R
Number of rack unit	1U
Cable length	8 ft (2.44 m)
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	RJ45 cable USB cable Country-specific detachable power cord Rack mounting brackets Rack mounting support rails Installation guide Warranty card

General

Redundant	No
-----------	----

Physical

Colour	Silver grey
Height	1.69 in (43 mm)
Width	17.01 in (432 mm)
Depth	22.05 in (560 mm)
Net weight	35.05 lb(US) (15.9 kg)
Mounting preference	No preference
Mounting mode	Rack-mounted with kit Tower-mounted with kit

Two post mountable	1
USB compatible	Yes
Input	
Network frequency	50/60 Hz
Output	
Maximum configurable power in W	2200 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	On-Line
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	2200 VA
Conformance	
Product certifications	UL/cUL listed FCC
Standards	UL 1778 CSA C22.2 No 107.3-05 FCC part 15 class A
Environmental	
Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dB
IP degree of protection	IP20
Batteries & Runtime	
Battery recharge time	1.5 h
Battery voltage	50 V
Battery charger power	448 W
Battery power in VAH	312 VAh runtime
Battery option	SRTL50RMBP1U-LI 1 1452 VAh SRTL50RMBP1U-LI 2 2592 VAh SRTL50RMBP1U-LI 3 3732 VAh SRTL50RMBP1U-LI 4 4872 VAh SRTL50RMBP1U-LI 5 6012 VAh
Extended runtime	1
Replacement battery	APCRBC173-LI 

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.95 in (278.2 mm)
Package 1 Width	22.20 in (564 mm)
Package 1 Length	30.08 in (764 mm)
Package 1 Weight	53.3 lb(US) (24.18 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

Recommended replacement(s)