## **BRIDLE RINGS MAGNETIC MOUNT**





BRM150-HD

BRM75WH

### **FEATURES**

• Easy to mount

#### **APPLICATION**

- Magnetic mount bridle rings are used to support communication cables and other low voltage wires on metal surface mount applications
- Southwire bridle rings allow a quick and inexpensive way to support non data sensitive wires and cables from structural members

### **MATERIAL/FINISH**

• Steel/Zinc plated

PART #	MATERIAL/COLOR	LOOP SIZE	CAT5E CABLE Capacity	PULL-OUT Strength	BOX QTY.
BRM75BK	Steel, painted black	3/4"	10	15 LBS.	100
BRM75WH	STEEL, PAINTED WHITE	3/4"	10	15 LBS.	100
BRM100BK	Steel, painted black	1"	20	15 LBS.	100
BRM100WH	STEEL, PAINTED WHITE	1"	20	15 LBS.	100
BRM125BK	Steel, painted black	1-1/4"	30	15 LBS.	100
BRM125WH	STEEL, PAINTED WHITE	1-1/4"	30	15 LBS.	100
BRM150-HD		1-1/2"	42	90 LBS.	50
BRM200-HD	ZINC PLATED STEEL	2"	73	90 LBS.	50
BRM400-HD		4"	250	90 LBS.	50

# **DISTRIBUTION RINGS** SURFACE MOUNT, METALLIC



DST-200

PART #	MATERIAL	CABLE I.D.	CAT5E CABLE CAPACITY	BOX QTY.
DST-200		2"	75	50
DST-300	ALUMINUM	3"	150	50
DST-500		5"	250	25
DST-800	ZINC PLATED STEEL	8"	425	25
DST-1200		12"	550	25

### **FEATURES**

- Distribution rings have a smooth surface
- that prevents cables from being damaged
- .22" diameter mounting holes

### APPLICATION

• Distribution rings are used when support for multiple vertical or horizontal cable runs is required on walls or ceilings

### **MATERIAL/FINISH**

- Aluminum
- Steel/Zinc plated